

Product data sheet

Specifications



TeSys Deca - auxiliary contact - 3 NO early-break

GV3A05

⚠ Discontinued on: Jan 23, 2021

⚠ Discontinued

Main

| | |
|---------------------------|-------------------------|
| Range | TeSys |
| Device short name | GV3A |
| Product or Component Type | Auxiliary contact block |
| Product Compatibility | GV3ME |
| Mounting Location | Right side |
| Pole contact composition | 3 NO |
| Quantity per Set | Set of 10 |

Complementary

| | |
|---|---|
| [Ui] rated insulation voltage | 600 V UL 508 690 V IEC 60947-1 600 V CSA C22.2 No 14 |
| [Ue] rated operational voltage | 48...690 V AC 24...220 V DC |
| [Ith] conventional free air thermal current | 6 A |
| Mechanical durability | 100000 cycles |
| Protection type | GB2CB... circuit breaker GG fuse 6 A |
| Rated operational power in VA | 350 VA 48 V AC-11 100000 cycles 700 VA 440 V AC-11 100000 cycles 700 VA 500 V AC-11 100000 cycles 400 VA 690 V AC-11 100000 cycles 500 VA 110...127 V AC-11 100000 cycles 800 VA 220...240 V AC-11 100000 cycles 850 VA 380...415 V AC-11 100000 cycles |
| Rated operational power in W | 180 W 24 V DC-11 100000 cycles 240 W 48 V DC-11 100000 cycles 180 W 60 V DC-11 100000 cycles 140 W 110 V DC-11 100000 cycles 120 W 220 V DC-11 100000 cycles |
| Net Weight | 0.15 lb(US) (0.07 kg) |

Environment

| | |
|------------------------------|--------------------|
| Environmental characteristic | Normal environment |
|------------------------------|--------------------|

Ordering and shipping details

| | |
|-------------------|----------------------------------|
| Category | 22366-MAN STR PROTECTORS-GV1/GV3 |
| Discount Schedule | I11 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|--------------------------|---------------|
| GTIN | 3389110343397 |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|-------------------------------|-----------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 0.6 in (1.5 cm) |
| Package 1 Width | 3.1 in (8 cm) |
| Package 1 Length | 3.7 in (9.5 cm) |
| Package weight(Lbs) | 1.6 oz (45 g) |

Contractual warranty

| | |
|-----------------------------|----|
| Warranty (in months) | 18 |
|-----------------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

[EU RoHS Directive](#)

Compliant

California proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.