

Product datasheet

Specifications



TeSys GF - impulse relay - 16 A - 2 NO - 24 V AC 50/60 Hz coil

Local distributor code:

380920509

GF1620B7

 **Discontinued on:** 15 Jun 2023

EAN Code: 3389110707809

 **Discontinued**

Main

Range	TeSys
Product name	TeSys GF
Product or component type	Impulse relay
Device short name	GF16
Utilisation category	AC-1
Poles description	2P
Pole contact composition	2 NO
[Ie] rated operational current	16 A AC-1
[Ue] rated operational voltage	250 V AC 50/60 Hz
Permissible short-time rating	320 A 40 °C 1 s 48 A 40 °C 30 s 96 A 40 °C 10 s
Operating position	+/- 90° to vertical plane
Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	24 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail

Complementary

[Ith] conventional free air thermal current	16 A (at 50 °C)
Average impedance	4 mOhm at 50 Hz - Ith 16 A
[Ui] rated insulation voltage	400 V conforming to IEC 60947-5-1 400 V conforming to VDE 0110
[Uimp] rated impulse withstand voltage	4 kV in enclosure
Connections - terminals	Control circuit: screw clamp terminals 1 cable(s) 1.5 mm ² solid without cable end Control circuit: screw clamp terminals 1 cable(s) 2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 2.5 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm ² solid without cable end Control circuit: screw clamp terminals 2 cable(s) 2.5 mm ² flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 0.5...6 mm ² flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 0.5...6 mm ² flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 0.5...6 mm ² solid without cable end Power circuit: screw clamp terminals 2 cable(s) 0.5...4 mm ² flexible with cable end Power circuit: screw clamp terminals 2 cable(s) 0.5...4 mm ² flexible without cable end Power circuit: screw clamp terminals 2 cable(s) 0.5...4 mm ² solid without cable end

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Tightening torque	Control circuit: 0.8 N.m - on screw clamp terminals Power circuit: 0.8 N.m - on screw clamp terminals
Operating time	70 ms closing 70 ms opening
Maximum operating rate	900 cyc/h
Control circuit voltage limits	0.85...1.1 Uc 50 °C 50/60 Hz
Impulse duration	>= 70 ms
Average consumption	19 VA AC 50 Hz at at Uc at 20 °C
Power dissipation per pole	1 W
Mechanical durability	1 Mcycles
Electrical durability	100000 cycles AC-22 200000 cycles AC-21
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	64 mm
Net weight	0.11 kg
Quantity per set	Set of 12

Environment

Standards	IEC 60669-1 NF C 61-112 IEC 60669-2
IP degree of protection	IP40 conforming to VDE 0106 (in enclosure) IP20 conforming to VDE 0106
Protective treatment	TC
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...80 °C
Operating altitude	<= 2000 m without derating
Mechanical robustness	Vibrations contactor open: 4 Gn, 5...300 Hz Vibrations contactor closed: 4 Gn, 5...300 Hz

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	9.2 cm
Package 1 Length	23.0 cm
Package 1 Weight	119.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.0 cm
Package 2 Width	9.2 cm
Package 2 Length	23.0 cm

Package 2 Weight	1.434 kg
Unit Type of Package 3	S02
Number of Units in Package 3	48
Package 3 Height	15.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	6.168 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	361e1245-bdfb-4c55-bca5-ee0430c46917
Halogen-free status	Halogen free plastic parts product

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
End of life manual availability	End of Life Information
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins