

Product datasheet

Specifications

Motors



AC servo motor BDH - 2.04 N.m -
8000 rpm - key shaft - without brake
- IP54

BDH0702D11A2A

⚠ Discontinued on: 8 Jul 2022

⚠ Discontinued

EAN Code: 3389118172401

Main

| | |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product or component type | AC servo motors |
| Component name | BDH |
| Continuous stall torque | 2.04 N.m for LXM15LD10N4 3 phases 2.04 N.m for LXM15LD13M3 3 phases 2.04 N.m for LXM15LD13M3 single phase |
| Peak stall torque | 6.51 N.m for LXM15LD10N4 at 230 V 3 phases 6.51 N.m for LXM15LD10N4 at 400 V 3 phases 6.51 N.m for LXM15LD10N4 at 480 V 3 phases 6.51 N.m for LXM15LD13M3 at 230 V 3 phases 6.51 N.m for LXM15LD13M3 at 230 V single phase |
| Nominal output power | 450 W for LXM15LD10N4 at 230 V 3 phases 450 W for LXM15LD13M3 at 230 V 3 phases 450 W for LXM15LD13M3 at 230 V single phase 750 W for LXM15LD10N4 at 400 V 3 phases 900 W for LXM15LD10N4 at 480 V 3 phases |
| Nominal torque | 1.51 N.m for LXM15LD10N4 at 480 V 3 phases 1.6 N.m for LXM15LD10N4 at 400 V 3 phases 1.82 N.m for LXM15LD10N4 at 230 V 3 phases 1.82 N.m for LXM15LD13M3 at 230 V 3 phases 1.82 N.m for LXM15LD13M3 at 230 V single phase |
| Nominal speed | 2300 rpm for LXM15LD10N4 at 230 V 3 phases 2300 rpm for LXM15LD13M3 at 230 V 3 phases 2300 rpm for LXM15LD13M3 at 230 V single phase 4500 rpm for LXM15LD10N4 at 400 V 3 phases 5500 rpm for LXM15LD10N4 at 480 V 3 phases |
| Maximum mechanical speed | 8000 rpm |
| Product compatibility | LXM15LD10N4 at 230 V 3 phases LXM15LD10N4 at 400 V 3 phases LXM15LD10N4 at 480 V 3 phases LXM15LD13M3 at 230 V 3 phases LXM15LD13M3 at 230 V single phase |
| Shaft end | Keyed |
| IP degree of protection | IP54 |
| Encoder type | Absolute single turn SinCos Hiperface |
| Speed feedback resolution | 1048576 points/turn |
| Holding brake | Without |
| Mounting support | International IEC standard flange |
| Electrical connection | Rotatable right-angled connectors |
| Number of poles | 8 |

Complementary

| | |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Range compatibility | Lexium 15 |
| Maximum current Irms | 6.29 A |
| Torque constant | 0.92 N.m/A at 120 °C |
| Back emf constant | 59 V/krpm at 120 °C |
| Stator resistance | 9.57 Ohm at 20 °C |
| Stator inductance | 20.1 mH at 20 °C |
| Stator electrical time constant | at 20 °C |
| Maximum radial force Fr | 150 N at 6000 rpm 165 N at 5000 rpm 180 N at 4000 rpm 200 N at 3000 rpm 240 N at 2000 rpm 300 N at 1000 rpm |
| Maximum axial force Fa | 0.3 x Fr |
| Net weight | 2.23 kg |



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No