

Product datasheet

Specifications



trip unit STR22ME for Compact NS 100/160/250 circuit breakers, electronic, rating 100 A, 3 poles 3d

29170

⚠ Discontinued on: 23 Jan 2021

⚠ Discontinued

Main

Range	ComPact
Range of product	NS100...250
Product or component type	Trip unit
Trip unit name	STR22ME
Trip unit technology	Electronic
Range compatibility	ComPact NS100
Device application	Motor
Number of poles	3P
Protected poles description	3t
Protection type	for overload protection (long time) for short time short-circuit protection
Trip unit rated current	100 A at 20 °C 90 A at 70 °C 95 A at 60 °C
Network type	AC
Network frequency	50/60 Hz

Complementary

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable 10 settings
[Ir] long-time protection pick-up adjustment range	0.6...1 x In
Long-time protection delay adjustment type tr	Fixed
[tr] long-time protection delay adjustment range	120...320 s at 1.5 x Ir 4...10 s at 7.2 x Ir 6...15 s at 6 x Ir
Short-time protection pick-up adjustment type Isd	Fixed
[Isd] Short-time protection pick-up adjustment range	13 x Ir
Short-time protection delay adjustment type tsd	Fixed
[tsd] Short-time protection delay adjustment range	0.01...0.06 s
Instantaneous protection pick-up adjustment type Ii	Fixed
Display type	LED

Environment

Standards	IEC 60947-2
Product certifications	ASTA LCIE ASEFA KEMA
Pollution degree	3 conforming to IEC 60947
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins