

Product datasheet

Specifications



TeSys fuse-disconnector + add on block - 3P-32A- fuse size 10x38mm - screw type

LS1D32AE20TQ

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

Range	TeSys
Product name	TeSys LS1
Product or component type	Fuse-disconnector
Device short name	LS1D
Device application	Control
Poles description	3P

Complementary

Mounting support	Rail
Mounting position	Vertical (tolerance: +/- 23°)
Control type	Toggle
[Ue] rated operational voltage	600 V
[Ie] rated operational current	32 A for power circuit
Contacts type and composition	1 NO + 1 NO
Local signalling	Blown fuse indication
Fuse size	10 x 38 mm
Fuse type	GG AM
Associated fuse rating	30 A aM 30 A gG
Connections - terminals	Screw clamp terminals 2 cable(s) 1...6 mm ² solid Screw clamp terminals 2 cable(s) 1...6 mm ² flexible without cable end Screw clamp terminals 2 cable(s) 1...4 mm ² flexible with cable end
Tightening torque	1.7 N.m on screw clamp terminals

Environment

Standards	IEC 60947-1 IEC 60947-2 IEC 60947-4-1
Product certifications	BV UR
Protective treatment	TH
Ambient air temperature for operation	-50...70 °C operation
Height	89 mm

Width	45 mm
Depth	68.3 mm
Net weight	0.3 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

[End of Life Information](#)

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins