

Product datasheet

Specifications



Interbus communication card

VW3A3E304

Main

Product or component type	Communication card
Range compatibility	Altivar 71 Plus Altivar 61 Plus
Communication port protocol	Interbus
Connector type	9-way female SUB-D connector 9-way male SUB-D connector

Complementary

Communication service	Communication monitoring I/O data Abort communication relationship Communication and drive status Identification of the card Initialize communication relationship Profile 21 Read object description Read parameter Write parameter
Supply	By drive but necessary to use an external supply if the inverter is not powered
Display type	1 LED for BA (periodic data) 1 LED for RC (bus input) 1 LED for Rd (bus output) 1 LED for TR (messaging) 1 LED for U (power supply) Graphic display terminal for control word received Graphic display terminal for reference received
Net weight	0.3 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.2 cm
Package 1 Width	17.0 cm
Package 1 Length	23.5 cm
Package 1 Weight	298.0 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No