

Product data sheet

Specifications



Auxiliary contacts, TeSys GS, 2 C/O, early break, front mounting, for GS1 50 to 400A with direct right handle

GS1AM2

❗ Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	TeSys
Device short name	GS1AM
Product or Component Type	Auxiliary contact
Contact application	O and I position signalling
Range compatibility	TeSys TeSys GS GS1 F fuse-switch disconnectors TeSys TeSys GS GS1G fuse-switch disconnectors TeSys TeSys GS GS1 J fuse-switch disconnectors TeSys TeSys GS GS1 K fuse-switch disconnectors TeSys TeSys GS GS1 L fuse-switch disconnectors TeSys TeSys GS GS1 N fuse-switch disconnectors TeSys TeSys GS GS1Q fuse-switch disconnectors
Contacts type and composition	2 C/O
Contact operation	Early-break
[Ith] conventional free air thermal current	16 A (at 104 °F (40 °C))
[Ie] rated operational current	5 A 127 V AC-15 4 A 230 V AC-15 3 A 400/415 V AC-15 2 A 440 V AC-15 12 A 24 V DC-13 2 A 48 V DC-13 0.6 A 110 V DC-13 0.4 A 220 V DC-13

Complementary

Mechanical durability	1 Mcycles
Electrical durability	30000 cycles AC-15
switch rated current	50 A 63 A 100 A 125 A 160 A 200 A 250 A 315 A 400 A
Fuse type	NFC DIN BS
Type of operating handle	Direct right side
Mounting Location	Front face
Net Weight	0.077 lb(US) (0.035 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	US1CP1018402
Discount Schedule	CP10
GTIN	3389110563221
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.756 in (7.000 cm)
Package 1 Width	1.181 in (3.000 cm)
Package 1 Length	3.937 in (10.000 cm)
Package weight(Lbs)	1.376 oz (39.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	20
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	5.906 in (15.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	34.321 oz (973.000 g)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.