

SITRANS P DS III, HART, 4-20 MA transmitter for absolute pressure from pressure transmitter series ***** Attention, product canceled / successor product P320/P420 available! Please get in touch with your Siemens contact to determine the successor product ***** Measuring cell filling silicone oil, normal cleaning Span: 43 to 1300 mbar a (0.62 to 18.9 psi a), overload limit 10 bar Diaphragm stainless steel measuring cell stainless steel Process connection: connection shank G1/2 B to EN 837-1 Die-cast aluminium housing Standard design None explosion protection Electric connection and cable inlet: cable gland M20 x 1.5 Housing cover with window (digital indicator visible, customized adjustment, supplement Y21 required) Plate inscription: english Test certificate according to standard IEC 60770-2 Range (linear characteristic) specify in plain text: Y01:...to ...mBar, kpa, mpa,... Stainless steel tag plate (measuring point description) Max.16 character, specify in plain text: Adjustment digital indicator specify in plain text Y21: mBar, bar, kpa, mpa, ...

Further information

Configurable Products

Technical Data and CAx data (3d-models , eplan.macros) from configurable products cannot shown here. To display the technical data for your device configuration please open PIA LifeCyclePortal and enter there your product number (MLFB). Exemplary 3d-models and eplan-macros are available at the industry imagadatabase. Data for a specific product can be requested with help of a support request.

PIA LifeCyclePortal

<https://pia-portal.automation.siemens.com>

Industry - Image Database

<http://www.automation.siemens.com/bilddb/>

Industry Mall (Online-Order System)

<https://mall.industry.siemens.com>

Information- and Downloadcenter (Catalogs, Brochures, ...)

<http://www.siemens.com/industrial-controls/catalogs>

Support Request

<https://support.industry.siemens.com/my/us/en/requests#createRequest>

last modified:

9/21/2024 