

# Product datasheet

Specifications



REL52110 discontinued. To order it, click on blue Product Selector button, configure P3U30, and use its output xml file

REL52110

! Discontinued

! Discontinued on: 13 Nov 2023

## Main

|                                       |                                                                                                                                                                        |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product                      | PowerLogic P3                                                                                                                                                          |
| Product or component type             | Protection relay                                                                                                                                                       |
| Relay application                     | Feeder                                                                                                                                                                 |
| product reference                     | P3F30-CGIAA-AAEDA-BBAAA                                                                                                                                                |
| Mounting case size                    | 30TE                                                                                                                                                                   |
| power supply                          | 48...230 V AC/DC                                                                                                                                                       |
| measuring inputs                      | : 1/5 A CT phase current 3<br>: 5/1 A CT residual current 1<br>: 1/0.2 A CT residual current 1<br>: 100 V/110 V VT voltage 4                                           |
| Number of sensors                     | 0 temperature sensor(s)<br>0 arc sensor(s)                                                                                                                             |
| number of Digital Inputs (DI)         | 16                                                                                                                                                                     |
| number of analogue inputs             | 0                                                                                                                                                                      |
| number of Digital Outputs (DO)        | 1 watchdog<br>9                                                                                                                                                        |
| number of analogue outputs            | 0                                                                                                                                                                      |
| type of temperature module connection | Copper cable external module<br>Fiber optic cable external module                                                                                                      |
| communication ports                   | USB port 1 front<br>LC 1 rear<br>RS232 1 rear                                                                                                                          |
| communication protocols               | IEC 61850 ed. 1<br>IEC 61850 ed. 2<br>IEC 60870-5-101<br>IEC 60870-5-103<br>DNP3<br>DNP3 TCP<br>Modbus RTU<br>Modbus TCP<br>EtherNet/IP<br>Modbus TCP master<br>SPABus |
| Cybersecurity                         | Password protection<br>Port hardening                                                                                                                                  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

|                       |                                               |
|-----------------------|-----------------------------------------------|
| protection functions  | Phase overcurrent 50/51                       |
|                       | Directional phase overcurrent 67              |
|                       | Earth fault overcurrent 50N/51N               |
|                       | Directional earth fault 67N                   |
|                       | Transient earth fault 67NI                    |
|                       | Capacitor bank unbalance 51C                  |
|                       | Broken conductor 46 I2/I1                     |
|                       | Cold load pick-up                             |
|                       | Switch ON to fault (SOTF)                     |
|                       | Breaker failure 50BF                          |
|                       | Directional active underpower 37P             |
|                       | Fault locator 21FL                            |
|                       | Recloser 79                                   |
|                       | Phase undercurrent 37                         |
|                       | Excessive starting time, locked rotor 48/51LR |
|                       | Motor restart inhibition 66                   |
|                       | Capacitor overvoltage 59C                     |
|                       | Negative sequence overcurrent 46              |
|                       | Overvoltage 59                                |
|                       | Undervoltage 27                               |
|                       | Positive sequence undervoltage 27P            |
|                       | Earth fault overvoltage 59N                   |
|                       | Underfrequency 81/81N                         |
|                       | Rate of change of frequency 81R               |
|                       | Synchro-check 25                              |
|                       | Lockout relay 86                              |
|                       | CT supervision 60                             |
|                       | VT supervision 60                             |
|                       | H2 detection 68H2                             |
|                       | H2 detection                                  |
|                       | H5 detection 68H5                             |
|                       | H5 detection                                  |
|                       | Programmable stages 99                        |
|                       | Programmable curve                            |
| Arc flash protection  | No                                            |
| measurement functions | Current 3-phase                               |
|                       | Current zero sequence                         |
|                       | Current positive sequence                     |
|                       | Current negative sequence                     |
|                       | Current ratio of negative and positive        |
|                       | Voltage phase to earth                        |
|                       | Voltage phase to phase                        |
|                       | Voltage zero sequence                         |
|                       | Voltage positive sequence                     |
|                       | Voltage negative sequence                     |
|                       | Voltage ratio of negative and positive        |
|                       | Short circuit fault reactance                 |
|                       | Fault location current                        |
|                       | Earth fault reactance                         |
|                       | Frequency                                     |
|                       | Active power                                  |
|                       | RMS active power                              |
|                       | Reactive power                                |
|                       | RMS reactive power                            |
|                       | Apparent power                                |
|                       | RMS apparent power                            |
|                       | Active energy                                 |
|                       | Reactive energy                               |
|                       | Cos $\varphi$                                 |
|                       | Tan $\varphi$                                 |
|                       | Power angle                                   |
|                       | Power factor                                  |
|                       | Voltage phasor diagram view                   |
|                       | Current phasor diagram view                   |
|                       | Current 2nd, 15th harmonics with THD          |
|                       | Voltage 2nd, 15th harmonics with THD          |
|                       | Voltage interruption                          |
|                       | Condition monitoring CB wear                  |

|                                 |                                                                                                                                                                                                                                                                             |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| control functions               | Switchgear control and monitoring<br>Programmable switchgear interlocking<br>Local control on single-line diagram<br>Local control with I/O keys<br>Local/remote control<br>2 function keys<br>Mobile application with Easergy SmartApp<br>Web-server<br>Programmable logic |
| controllable switchgear devices | 6 controlled + 8 displayed                                                                                                                                                                                                                                                  |
| number of setting groups        | 4                                                                                                                                                                                                                                                                           |
| monitoring functions            | Trip circuit supervision 74<br>Circuit breaker monitoring<br>Relay self-monitoring                                                                                                                                                                                          |
| logs and records                | Event recording<br>Disturbance recording<br>Tripping context                                                                                                                                                                                                                |
| Switchgear diagnosis type       | CT/VT supervision ANSI code: 60<br>CT supervision<br>Trip circuit supervision ANSI code: TCS                                                                                                                                                                                |
| Connections - terminals         | Screw removable (digital input/output)<br>Pin fixed (current transformer)<br>Pin removable (voltage transformer)                                                                                                                                                            |

## Complementary

|                               |                                                |
|-------------------------------|------------------------------------------------|
| Operating threshold           | 110...230 V AC/DC                              |
| Time synchronisation protocol | SNTP<br>IRIG-B                                 |
| Software name                 | EcoStruxure Power Device<br>ESetup Easergy Pro |
| Web server                    | Embedded HTTP server                           |
| Display type                  | LCD 128 x 128 pixels with single line diagram  |
| Number of key                 | 2 customizable                                 |
| Local signalling              | 2 LEDs<br>16 LEDs programmable                 |
| Standards                     | IEC                                            |
| Height                        | 176 mm                                         |
| Width                         | 270 mm                                         |
| Depth                         | 230 mm                                         |
| Net weight                    | 4.2 kg maximum                                 |

## Environment

|                       |                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| climatic withstand    | Exposure to dry heat Bb tests conforming to EN/IEC 60068-2-2<br>Exposure to cold Ad tests conforming to EN/IEC 60068-2-1<br>Exposure to damp heat in service Db tests conforming to EN/IEC 60068-2-30<br>Exposure to damp heat in service Cab tests conforming to EN/IEC 60068-2-78                                                                                                    |
| Mechanical robustness | Vibrations (level: class II) conforming to IEC 60255-21-1<br>Vibrations: Fc conforming to IEC 60068-2-6<br>Shocks (level: class II) conforming to IEC 60255-21-2<br>Shocks: Ea conforming to IEC 60068-2-27<br>Seismic tests method A (level: class II) conforming to IEC 60255-21-3<br>Bumps (level: class II) conforming to IEC 60255-21-2<br>Bumps: Ea conforming to IEC 60068-2-27 |

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electromagnetic compatibility         | Emission tests conforming to IEC/EN 60255-26 ed. 3<br>Emission tests conforming to CISPR 11<br>Emission tests conforming to CISPR 22<br>EMC immunity conforming to IEC/EN 60255-26 ed. 3<br>EMC immunity conforming to EN/IEC 61000-4-18<br>EMC immunity level 4 conforming to EN/IEC 61000-4-2<br>EMC immunity level 3 conforming to EN/IEC 61000-4-3<br>EMC immunity level 4 conforming to EN/IEC 61000-4-4<br>EMC immunity level 3 conforming to EN/IEC 61000-4-5<br>EMC immunity level 3 conforming to EN/IEC 61000-4-6<br>EMC immunity conforming to EN/IEC 61000-4-8<br>EMC immunity level 5 conforming to EN/IEC 61000-4-9<br>EMC immunity conforming to EN/IEC 61000-4-29<br>EMC immunity conforming to EN/IEC 61000-4-11<br>EMC immunity conforming to EN/IEC 61000-4-17 |
| Ambient air temperature for operation | -40...65 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Ambient air temperature for storage   | -40...70 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| IP degree of protection               | IP54 conforming to IEC 60529                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| maximum operating altitude            | 2000 m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Protective treatment                  | Conformal coating                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Relative humidity                     | 0...95 %, without condensation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 26 cm   |
| Package 1 Width              | 21 cm   |
| Package 1 Length             | 31.5 cm |
| Package 1 Weight             | 5.2 kg  |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)


[How we assess product sustainability >](#)

### Use Better

| Materials and Substances |                                        |
|--------------------------|----------------------------------------|
| EU RoHS Directive        | <a href="#">Compliant By Exemption</a> |

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |



Dimensions Drawings

Base Unit Dimensions

