

Product data sheet

Specifications

SQUARE D



DRUM SWITCH 600VAC 7.5HP B +OPTIONS

2601BW1B

⚠ Discontinued

Main

Device short name B

Complementary

Cam switch function Reversing switch

Depth 6.89 in (175.006 mm)

Device Application Manual reversing control

Device mounting Flush

Electrical Connection Screw clamp terminal

Enclosure Material Brushed stainless steel

Enclosure type Water resistant enclosure indoor/outdoor
Dustproof enclosure indoor/outdoor

Height 5.5 in (139.7 mm)

Maximum Horse Power Rating 3 hp 230 V AC, 1 phase
5 hp 460/575 V AC, 3 phase
7.5 hp 460/575 V AC, 1 phase
1.5 hp 200/230 V AC, 3 phase
5 hp 115 V AC, 1 phase

Number of poles 3

Permissible voltage 600 V AC
250 V DC

Type of operator Ball bearing plunger
Drive shaft

Width 4.4 in (111.8 mm)

Environment

NEMA Degree of Protection NEMA 4

Product Certifications UL Listed
CSA

Ordering and shipping details

Category 21116-2601

Discount Schedule CP1

Returnability No

Country of origin MX

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package weight(Lbs)	2.701 lb(US) (1.225 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No