



Figure similar

RCBO, 6 kA, 1-pole+N, type AC, 30 mA, C char, In: 8 A, Un AC: 230 V, permitted in all countries. Observe national installation regulations!

Model	
product brand name	SENTRON
product designation	RCBO
design of the product	Instantaneous
General technical data	
number of poles	2
number of poles with protection	1
design of pole	1P+N
tripping characteristic class	C
mechanical service life (operating cycles) typical	10 000
overvoltage category	3
degree of pollution	2
Voltage	
type of voltage of the operating voltage	AC
insulation voltage (Ui) rated value	264 V
surge voltage resistance rated value	4 000 V
surge current resistance at (8/20) µs	1 kA
tripping fault current rated value	30 mA
• operational current	
— at 30 °C rated value	8 A
— at 40 °C rated value	7.52 A
— at 45 °C rated value	7.28 A
— at 50 °C rated value	6.96 A
— at 55 °C rated value	6.48 A
— at 60 °C rated value	6.48 A
— at 65 °C rated value	6.16 A
— at 70 °C rated value	5.84 A
• operational current at AC rated value	8 A
residual current type	AC
Supply voltage	
supply voltage	
• at AC rated value	230/240 V
• for testing equipment minimum	195 V
operating frequency	50 Hz
supply voltage frequency rated value	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors

Breaking Capacity		
switching capacity current		
• according to EN 60898 rated value • according to IEC 60947-2 rated value	6 kA 15 kA	
short-circuit current breaking capacity (Icn) according to EN 61009-1 rated value	6 kA	
rated residual switching capacity (IΔm) according to IEC 61009-1	6 kA	
energy limitation class	3	
Dissipation		
power loss [W]		
• maximum	1.2 W	
Product details		
product feature touch protection	Yes	
product component neutral conductor switching	Yes	
product feature halogen-free	Yes	
product feature silicon-free	Yes	
Connections		
connectable conductor cross-section solid		
• minimum • maximum	0.75 mm² 35 mm²	
connectable conductor cross-section stranded		
• minimum • maximum	0.75 mm² 35 mm²	
connectable conductor cross-section finely stranded with core end processing		
• minimum • maximum	0.75 mm² 25 mm²	
tightening torque with screw-type terminals		
• minimum • maximum	2.5 N·m 3 N·m	
position of power supply cord	Either top or bottom	
Mechanical Design		
height	90 mm	
width	36 mm	
depth	77 mm	
installation depth	70 mm	
number of modular width units	2	
mounting position	any	
Net Weight	269 g	
Environmental conditions		
influence of the surrounding temperature	Max. 95% humidity	
ambient temperature during operation		
• minimum • maximum	-25 °C 55 °C	
ambient temperature during storage		
• minimum • maximum	-40 °C 75 °C	
number of test cycles for environmental testing according to IEC 60068-2-30	28	
Approvals Certificates		
Environment	General Product Approval	
Environmental Confirmations	Environmental Confirmations	
		
Miscellaneous	Miscellaneous	
General Product Approval	EMV	Test Certificates



[Confirmation](#)



[Miscellaneous](#)

Test Certificates	other	Railway
-------------------	-------	---------

[Special Test Certificate](#)

[Miscellaneous](#)



[Confirmation](#)

[Miscellaneous](#)

[Special Test Certificate](#)

Railway	Dangerous goods
---------	-----------------

[Confirmation](#)

[Transport Information](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1356-1KK08>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SU1356-1KK08>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1356-1KK08

CAX-Online-Generator


<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>



last modified:

7/22/2025 

