

# Product datasheet

Specifications



## circuit breaker Compact NSX630HB2 - Micrologic 1.3 M - 500 A - 3 poles 3d

LV433742

 **Discontinued on:** 30 Jun 2023

 **Discontinued**

### Main

|                                                      |                                                                                                                                                                                         |
|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                                | ComPact                                                                                                                                                                                 |
| Product name                                         | ComPact NSX                                                                                                                                                                             |
| Range of product                                     | ComPact NSX400...630                                                                                                                                                                    |
| Device short name                                    | NSX630HB2                                                                                                                                                                               |
| Product or component type                            | Circuit breaker                                                                                                                                                                         |
| Device application                                   | Motor                                                                                                                                                                                   |
| Number of poles                                      | 3P                                                                                                                                                                                      |
| Protected poles description                          | 3t                                                                                                                                                                                      |
| [In] rated current                                   | 500 A at 65 °C                                                                                                                                                                          |
| [Ue] rated operational voltage                       | 690 V AC 50/60 Hz                                                                                                                                                                       |
| Network type                                         | AC                                                                                                                                                                                      |
| Network frequency                                    | 50/60 Hz                                                                                                                                                                                |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2                                                                                                                                                        |
| Utilisation category                                 | Category A                                                                                                                                                                              |
| [Icu] rated ultimate short-circuit breaking capacity | 100 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level                                    | HB2 100 kA 690 V AC                                                                                                                                                                     |
| Trip unit name                                       | MicroLogic 1.3 M                                                                                                                                                                        |
| Trip unit technology                                 | Electronic                                                                                                                                                                              |
| Trip unit protection functions                       | I                                                                                                                                                                                       |
| Control type                                         | Toggle                                                                                                                                                                                  |
| Circuit breaker mounting mode                        | Fixed                                                                                                                                                                                   |

### Complementary

|                                                     |                                                                                                                                                                             |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage                       | 800 V AC 50/60 Hz                                                                                                                                                           |
| [Uimp] rated impulse withstand voltage              | 8 kV                                                                                                                                                                        |
| [Ics] rated service short-circuit breaking capacity | 100 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>100 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                               | 15000 cycles                                                                                                                                                                |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                        |                                                                                                              |
|--------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Electrical durability                                  | 2000 cycles at 690 V In<br>6000 cycles at 690 V In/2<br>4000 cycles at 440 V In<br>8000 cycles at 440 V In/2 |
| Mounting support                                       | Backplate                                                                                                    |
| Upside connection                                      | Front                                                                                                        |
| Downside connection                                    | Front                                                                                                        |
| Connection pitch                                       | 45 mm                                                                                                        |
| Protection type                                        | I : for short-circuit protection (magnetic)                                                                  |
| Trip unit rating                                       | 500 A at 65 °C                                                                                               |
| Short-time protection pick-up adjustment type Isd      | Adjustable 9 settings                                                                                        |
| [Isd] Short-time protection pick-up adjustment range   | 3000 A<br>3500 A<br>4500 A<br>2500 A<br>5000 A<br>6500 A<br>5500 A<br>4000 A<br>6000 A                       |
| Short-time protection delay adjustment type tsd        | Fixed                                                                                                        |
| Instantaneous protection pick-up adjustment type Ii    | Fixed                                                                                                        |
| [Ii] instantaneous protection pick-up adjustment range | 6500 A                                                                                                       |
| Earth-leakage protection                               | Without                                                                                                      |
| Zone selective interlocking ZSI                        | Without                                                                                                      |
| Number of slots for electrical auxiliaries             | 6 slot(s)                                                                                                    |
| Local signalling                                       | Flashing LED (green) for ready to operate                                                                    |
| Width (W)                                              | 140 mm                                                                                                       |
| Height (H)                                             | 255 mm                                                                                                       |
| Depth (D)                                              | 110 mm                                                                                                       |
| Net weight                                             | 6.2 kg                                                                                                       |

## Environment

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Standards                             | EN/IEC 60947                                                 |
| Product certifications                | CCC<br>EAC<br>Marine                                         |
| Overvoltage category                  | Class II                                                     |
| Electrical shock protection class     | Class II                                                     |
| Pollution degree                      | 3 conforming to IEC 60664-1                                  |
| IP degree of protection               | IP40 conforming to IEC 60529                                 |
| IK degree of protection               | IK07 conforming to IEC 62262                                 |
| Ambient air temperature for operation | -25...70 °C                                                  |
| Ambient air temperature for storage   | -50...85 °C                                                  |
| Relative humidity                     | 0...95 %                                                     |
| Operating altitude                    | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 15.0 cm  |
| Package 1 Width              | 15.5 cm  |
| Package 1 Length             | 29.0 cm  |
| Package 1 Weight             | 5.688 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 1 035 kg CO2 eq.                              |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |
| Carbon footprint of the manufacturing phase [A1 to A3] | 30 kg CO2 eq.                                 |
| Carbon footprint of the distribution phase [A4]        | 1 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]        | 0.6 kg CO2 eq.                                |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 1 002 kg CO2 eq.                              |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0.9 kg CO2 eq.                                |

## Use Better



### Materials and Substances

|                   |                                        |
|-------------------|----------------------------------------|
| SCIP Number       | 25ca3248-85d0-423a-a9d8-5b7aeb52e7b6   |
| EU RoHS Directive | <a href="#">Compliant By Exemption</a> |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| End of life manual availability | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |