


Hybrid cables (One-Motor Cable connectivity) (Continued)

Designation	Description	From servo motor	To servo drive	Composition	Length		Reference	Weight	
					m	ft.		kg	lb
Hybrid cables for "One-Motor Cable connectivity"	Shielded cables equipped with a Quick lock M40 connector (servo motor end) and an RJ45 connector for the Encoder and free leads for Motor and holding brake (servo drive end)	SH3 "One-Motor Cable"	LXM62DD15C21000 LXM62DD15G21000 LXM62DD15D21000 LXM62DD15E21000 LXM62DD15H21000 LXM62DD15F21000 LXM62DD27C21000 LXM62DD27G21000 LXM62DD27D21000 LXM62DD27E21000 LXM62DD27H21000 LXM62DD27F21000	4x 2.5 mm ² + 2x 1.0 mm ² + 2x AWG 24	2	6.56	VW3ED145R020	1.020	2.25
					3	9.84	VW3ED145R030	1.310	2.89
					4	13.12	VW3ED145R040	1.590	3.51
					5	16.40	VW3ED145R050	1.880	4.14
					8	26.25	VW3ED145R080	2.740	6.04
					10	32.81	VW3ED145R100	3.310	7.30
					15	49.213	VW3ED145R150	4.740	10.45
					20	65.617	VW3ED145R200	6.170	13.60
					25	82.021	VW3ED145R250	7.600	16.76
					30	98.425	VW3ED145R300	9.030	19.91
					35	114.829	VW3ED145R350	10.460	23.06
					40	131.234	VW3ED145R400	11.890	26.21
					45	147.638	VW3ED145R450	13.320	29.37
					50	164.042	VW3ED145R500	14.750	32.52



Hybrid cable extensions (One-Motor Cable connectivity)

Designation	Description	For use with cables	Length		Reference	Weight	
			m	ft.		kg	lb
Hybrid cable extensions for "One-Motor Cable connectivity"	Shielded cables equipped with two Quick lock M17 male/female connectors	VW3ED132R●●● cables	5	16.40	VW3EF132R050	1.110	2.45
			10	32.81	VW3EF132R100	2.160	4.76
			15	49.213	VW3EF132R150	3.200	7.05
			20	65.617	VW3EF132R200	4.250	9.37
			30	98.425	VW3EF132R300	6.340	13.98
			40	131.234	VW3EF132R400	8.430	18.58
	Shielded cables equipped with two Quick lock M23 male/female connectors	VW3ED143R●●● cables	50	164.042	VW3EF132R500	10.520	23.19
			5	16.40	VW3EF143R050	1.320	2.91
			10	32.81	VW3EF143R100	2.370	5.22
			15	49.213	VW3EF143R150	3.300	7.28
			20	65.617	VW3EF143R200	4.460	9.83
			30	98.425	VW3EF143R300	6.550	14.44
	Shielded cables equipped with two Quick lock M23 male/female connectors	VW3ED144R●●● cables	40	131.234	VW3EF143R400	8.640	19.05
			50	164.042	VW3EF143R500	10.730	23.66
			5	16.40	VW3EF144R050	1.710	3.77
			10	32.81	VW3EF144R100	3.140	6.92
			15	49.213	VW3EF144R150	4.400	9.70
			20	65.617	VW3EF144R200	6.000	13.23
	Shielded cables equipped with two Quick lock M40 male/female connectors	VW3ED145R●●● cables	30	98.425	VW3EF144R300	8.860	19.53
			40	131.234	VW3EF144R400	11.720	25.84
			50	164.042	VW3EF144R500	14.580	32.14
			5	16.40	VW3EF145R050	2.360	5.20
			10	32.81	VW3EF145R100	3.790	8.36
			15	49.213	VW3EF145R150	4.700	10.36
			20	65.617	VW3EF145R200	6.650	14.66
			30	98.425	VW3EF145R300	9.510	20.97
			40	131.234	VW3EF145R400	12.370	27.27
			50	164.042	VW3EF145R500	15.230	33.58

