

# Product data sheet

Specifications



SH3 servomotor, 55mm, 1 stack,  
smooth Shaft, SinCos Singleturn  
128, no Brake, angular, IP54/65

SH30551P01A2000

Product availability: Non-Stock - Not normally stocked in  
distribution facility

## Main

|                           |             |
|---------------------------|-------------|
| Range Compatibility       | PacDrive 3  |
| Device short name         | SH3         |
| Product or Component Type | Servo motor |

## Complementary

|                           |                                                                                                                                                                            |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Maximum mechanical speed  | 9000 rpm                                                                                                                                                                   |
| [Us] rated supply voltage | 115...480 V                                                                                                                                                                |
| Phase                     | Three phase                                                                                                                                                                |
| Continuous stall current  | 0.73 A                                                                                                                                                                     |
| Continuous stall torque   | 3.72 lbf.in (0.42 N.m) 115...480 V three phase                                                                                                                             |
| Continuous power          | 290 W                                                                                                                                                                      |
| Peak stall torque         | 13.3 lbf.in (1.5 N.m) 115...480 V three phase                                                                                                                              |
| Nominal output power      | 100 W 115 V single phase<br>210 W 230 V single phase<br>400 W 400 V three phase<br>440 W 480 V three phase                                                                 |
| Nominal torque            | 4.4 lbf.in (0.5 N.m) 115 V single phase<br>4.4 lbf.in (0.5 N.m) 230 V single phase<br>3.10 lbf.in (0.35 N.m) 400 V three phase<br>3.10 lbf.in (0.35 N.m) 480 V three phase |
| Nominal speed             | 2000 rpm 115 V single phase<br>4000 rpm 230 V single phase<br>8000 rpm 400 V three phase<br>8000 rpm 480 V three phase                                                     |
| Maximum current Irms      | 2.9 A                                                                                                                                                                      |
| Shaft end                 | Smooth shaft                                                                                                                                                               |
| Shaft diameter            | 0.4 in (9 mm)                                                                                                                                                              |
| Shaft length              | 0.8 in (20 mm)                                                                                                                                                             |
| IP degree of protection   | IP54 shaft bushing without shaft seal ring: conforming to IEC 60034-5<br>IP65 motor: conforming to IEC 60034-5<br>IP65 shaft bushing: conforming to IEC 60034-5            |
| Encoder type              | Absolute single turn SinCos Hiperface                                                                                                                                      |
| Speed feedback resolution | 128 periods                                                                                                                                                                |
| Holding brake             | Without                                                                                                                                                                    |
| Mounting Support          | International standard flange                                                                                                                                              |
| Motor flange size         | 2.2 in (55 mm)                                                                                                                                                             |
| Electrical Connection     | Straight connector                                                                                                                                                         |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                       |                                                                                                                                              |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Torque constant                       | 0.58 N.m/A 248 °F (120 °C)                                                                                                                   |
| Back emf constant                     | 40 V/krpm 68 °F (20 °C)                                                                                                                      |
| Number of motor poles                 | 3.0                                                                                                                                          |
| Rotor inertia                         | 0.059 kg.cm²                                                                                                                                 |
| Stator resistance                     | 41.8 Ohm                                                                                                                                     |
| Stator inductance                     | 37.13 mH                                                                                                                                     |
| Maximum radial force Fr               | 340 N 1000 rpm<br>270 N 2000 rpm<br>240 N 3000 rpm<br>220 N 4000 rpm<br>200 N 5000 rpm<br>190 N 6000 rpm<br>180 N 7000 rpm<br>170 N 8000 rpm |
| Maximum axial force Fa                | 40 N                                                                                                                                         |
| Type of cooling                       | Natural convection                                                                                                                           |
| Length                                | 5.2 in (132.5 mm)                                                                                                                            |
| Centring collar diameter              | 1.6 in (40 mm)                                                                                                                               |
| Centring collar depth                 | 0.08 in (2 mm)                                                                                                                               |
| Number of mounting holes              | 4                                                                                                                                            |
| Mounting holes diameter               | 0.2 in (5.5 mm)                                                                                                                              |
| Circle diameter of the mounting holes | 2.5 in (63 mm)                                                                                                                               |
| Net Weight                            | 2.6 lb(US) (1.2 kg)                                                                                                                          |
| Sizing reference                      | SH30551P                                                                                                                                     |
| Network number of phases              | 3                                                                                                                                            |
| Temperature copper hot                | 266 °F (130 °C)                                                                                                                              |
| Electrical connection                 | rotatable right angled connector                                                                                                             |
| Output current 3s peak                | 2.9 A                                                                                                                                        |
| Inertia                               | 0.0 kg.cm² of brake<br>0.059 kg.cm² of motor                                                                                                 |

## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US1PC5218359  |
| Discount Schedule | PC52          |
| GTIN              | 3606485295039 |
| Returnability     | Yes           |
| Country of origin | DE            |

## Packing Units

|                        |                         |
|------------------------|-------------------------|
| Unit Type of Package 1 | PCE                     |
| Nbr. of units in pkg.  | 1                       |
| Package 1 Height       | 4.3 in (11.0 cm)        |
| Package 1 Width        | 7.5 in (19.0 cm)        |
| Package 1 Length       | 15.6 in (39.5 cm)       |
| Package weight(Lbs)    | 3.543 lb(US) (1.607 kg) |

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 2       | S04                      |
| Number of Units in Package 2 | 3                        |
| Package 2 Height             | 11.8 in (30 cm)          |
| Package 2 Width              | 15.7 in (40 cm)          |
| Package 2 Length             | 23.6 in (60 cm)          |
| Package 2 Weight             | 12.425 lb(US) (5.636 kg) |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                |
|--------------------------------------------------------|----------------|
| Total lifecycle Carbon footprint                       | 960 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 7 kg CO2 eq.   |
| Carbon footprint of the distribution phase [A4]        | 0.2 kg CO2 eq. |
| Carbon footprint of the installation phase [A5]        | 0 kg CO2 eq.   |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 952 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0.2 kg CO2 eq. |

## Use Better



### Materials and Substances

|                                        |                                                                                                                                                                                                                                                                 |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                                                                                                                                                                                             |
| Packaging without single use plastic   | No                                                                                                                                                                                                                                                              |
| <a href="#">EU RoHS Directive</a>      | Pro-active compliance (Product out of EU RoHS legal scope)                                                                                                                                                                                                      |
| SCIP Number                            | Ead0850d-370a-47c5-8cf7-1d93c2c974a4                                                                                                                                                                                                                            |
| REACH Regulation                       | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                               |
| California proposition 65              | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="#">www.P65Warnings.ca.gov</a> |
| PVC free                               | Yes                                                                                                                                                                                                                                                             |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                     |                                          |
|---------------------|------------------------------------------|
| Circularity Profile | No need of specific recycling operations |
| Take-back           | No                                       |