

Product datasheet

Specifications

Terminal shrouds, GoPact MTS 630, 400-630A



GMSISOTS04

Main

Range of product	GoPact MTS
Product or component type	Terminal shroud
Device application	Insulation
Range compatibility	GoPact MTS 630
[In] rated current	400...630 A
Frame size	4
Poles description	4P
Quantity per set	2

Complementary

Mounting location	Upstream Downstream
IP degree of protection	IP2X conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.2 cm
Package 1 Width	16 cm
Package 1 Length	37 cm
Package 1 Weight	0.35 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Packaging

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Longer

Lifetime extension

Repair	No
--------	----

Use Again

Repack and remanufacture

Take-back	No
-----------	----

Technical Illustration

Assembly's dimensions

