

Product datasheet

Specifications



DOL combination starter , TeSys Deca, 0.16...0.25 A , 24 V DC

GV2DM102BL

EAN Code: 3389110058123

! Discontinued

Main

| | |
|------------------------------|--|
| Range of product | TeSys Deca |
| Device short name | GV2DM |
| Product or component type | Motor starter |
| Motor starter type | Non reversing |
| Coordination type | Type 1 Type 2 |
| Poles description | 3P |
| Utilisation category | AC-3 |
| Motor power kW | 0.06 kW at 400...415 V AC 50/60 Hz 0.06 kW at 440 V AC 50/60 Hz |
| [Uc] control circuit voltage | 24 V DC |
| Magnetic tripping current | 2.4 A |

Complementary

| | |
|-------------------------------------|---|
| Device composition | 1 3-pole contactor LC1D 1 motor circuit breaker type GV2ME 1 combination block GV2AF3 |
| Thermal protection adjustment range | 0.16...0.25 A |
| Rated breaking capacity | Iq 50 kA at 400...415 V conforming to IEC 60947-4-1 Iq 50 kA at 440 V conforming to IEC 60947-4-1 Iq 50 kA at 500 V conforming to IEC 60947-4-1 |
| Net weight | 0.596 kg |
| Height | 176.4 mm |
| Width | 45 mm |
| Depth | 99.6 mm |

Packing Units

| | |
|------------------------------|-----|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No