

Product datasheet

Specifications



TeSys LF - enclosed DOL reversing starter - 2.5...4 A - HARTING - UL

LF4MP08EA74U

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

| | |
|-------------------------------------|--|
| Range | TeSys |
| Product name | TeSys LF |
| Device short name | LF4MP |
| Product or component type | Enclosed DOL reversing starter |
| Device application | AS interface |
| Device composition | Reversing contactor AS interface module Circuit-breaker |
| Utilisation category | AC-3 |
| Network type | AC |
| [Uc] control circuit voltage | 24 V AC 50/60 Hz |
| Thermal protection adjustment range | 2.5...4 A |
| Control type | Rotary handle for protection control - OFF - Trip - ON Selector switch 3 positions for start/stop/start - 1 - 0 - 2 |

Complementary

| | |
|--|---|
| Motor power kW | 0.75 kW at 220/230 V AC 50/60 Hz 1.5 kW at 400/415 V AC 50/60 Hz |
| Network frequency | 50/60 Hz |
| [Ue] rated operational voltage | Power circuit: 415 V AC 50/60 Hz Output control relay: 250 V AC 50/60 Hz Output control relay: 30 V DC |
| [Uimp] rated impulse withstand voltage | 6 kV for power circuit conforming to IEC 60947-1 2.5 kV for 24 V conforming to IEC 60947-1 2.5 kV for sensor conforming to IEC 60947-1 2.5 kV for AS-Interface conforming to IEC 60947-1 |
| Insulation resistance | > 1000 mOhm for output and communication |
| Insulation | 1500 V between output and ground 1500 V between output and internal logic between input and communication |
| [Ui] rated insulation voltage | 415 V AC 50/60 Hz conforming to IEC 60947 |
| [Ithe] conventional enclosed thermal current | 5 A for output control relay at 40 °C |
| Protection type | Inductive overvoltage Phase failure Thermal protection Short-circuit protection (magnetic) |
| Breaking capacity | 100 kA at 230/240 V conforming to IEC 60947-2 100 kA at 400/415 V conforming to IEC 60947-2 |

| | |
|--------------------------------------|--|
| Mechanical durability | 0.1 Mcycles for circuit breaker 30 Mcycles for contactor |
| Electrical durability | Circuit breaker: 0.1 Mcycles Contactor: 0.8 Mcycles - AC-3 - 8.5 A Relay: 0.1 Mcycles - 24 V, operating rate <6 cyc/mn - AC-12 - 5 A Relay: 1 Mcycles - 24 V, operating rate <15 cyc/mn - AC-12 - 1 A Relay: 0.5 Mcycles - 24 V, operating rate <15 cyc/mn - AC-14 - 1 A Relay: 1 Mcycles - 24 V, operating rate <15 cyc/mn - AC-14 - 0.5 A Relay: 5 Mcycles - 24 V, operating rate <30 cyc/mn - AC-14 - 0.25 A Relay: 0.1 Mcycles - 24 V, operating rate <6 cyc/mn - DC-12 - 5 A Relay: 0.2 Mcycles - 24 V, operating rate <6 cyc/mn - DC-12 - 2 A Relay: 0.5 Mcycles - 24 V, operating rate <15 cyc/mn - DC-3 - 1 A Relay: 1 Mcycles - 24 V, operating rate <30 cyc/mn - DC-3 - 0.25 A |
| Current consumption | 20 mA for communication bus during operation 60 mA for communication bus sensor 0 mA at 24 V for supply circuit de-energisation 30 mA at 24 V for supply circuit maintained mode 110 mA at 24 V for supply circuit inrush 20 mA for output relay |
| Local signalling | Product status: 3 LEDs Input/output status: LED |
| Number of inputs | 2 M12 |
| nominal input value | 19...30 V 50 mA - DC |
| Input description | Status D0: forward stop - bit value 0 Status D1: reverse stop - bit value 0 Status D2: disable relay - bit value 0 Status D3: unused - bit value 0 Status D0: forward start - bit value 1 Status D1: reverse start - bit value 1 Status D2: enable relay - bit value 1 Status D3: unused - bit value 1 |
| Input type | Resistive |
| sensor compatibility | 2 or 3-wire PNP |
| Output description | Command D0: not ready - bit value 0 Command D1: stopped - bit value 0 Command D2: sensor 1 missing - bit value 0 Command D3: sensor 2 missing - bit value 0 Command D0: ready - bit value 1 Command D1: started - bit value 1 Command D2: sensor 1 present - bit value 1 Command D3: sensor 2 present - bit value 1 |
| Response time | <= 10 ms closing for output control relay <= 15 ms opening for output control relay |
| Contacts type and composition | 1 C/O |
| AS-interface profile | 7A70 - extended A/B |
| Connections - terminals | Power circuit: screw clamp terminals 1 x 1.5...2 x 4 mm ² - rigid Power circuit: screw clamp terminals 1 x 1.5...2 x 4 mm ² - flexible without cable end Power circuit: screw clamp terminals 1 x 1.5...2 x 2.5 mm ² - flexible with cable end Output control relay: HARTING socket Supply circuit: HARTING socket |
| Tightening torque | Power circuit: 0.8 N.m - with screwdriver flat Ø 5.5 mm |
| Width | 279 mm |
| Height | 245 mm |
| Depth | 179 mm |
| Net weight | 1.6 kg |

Environment

| | |
|--------------------------------------|---|
| Electromagnetic compatibility | <p>Electrostatic discharge - test level: 8 kV level 3 (in air) conforming to EN/IEC 61000-4-2</p> <p>Electrostatic discharge - test level: 4 kV level 2 (in indirect mode) conforming to EN/IEC 61000-4-2</p> <p>Surge immunity test - test level: 4 kV level 4 (power, line to ground) conforming to IEC 61000-4-5</p> <p>Surge immunity test - test level: 2 kV level 4 (power, line to line) conforming to EN/IEC 61000-4-5</p> <p>Surge immunity test - test level: 2 kV level 2 (control circuit, line to ground) conforming to IEC 61000-4-5</p> <p>Surge immunity test - test level: 500 V level 2 (control circuit, line to line) conforming to EN/IEC 61000-4-5</p> <p>Electrical fast transient/burst immunity test - test level: 2 kV level 3 conforming to EN/IEC 61000-4-4</p> <p>Conducted RF disturbances - test level: 10 V/m conforming to IEC 61000-4-6</p> <p>Conducted RF disturbances - test level: 10 V/m conforming to ENV 50141</p> <p>Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m conforming to IEC 61000-4-3</p> <p>Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m conforming to ENV 50204</p> <p>Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m conforming to ENV 50140</p> <p>Disturbing field emission class B conforming to ENV 55011</p> <p>Disturbing field emission class B conforming to CISPR 11</p> |
|--------------------------------------|---|

| | |
|------------------------------|---|
| Mechanical robustness | <p>Shocks contactor open - 10 Gn conforming to IEC 60068-2-27</p> <p>Shocks contactor closed - 15 gn conforming to IEC 60068-2-27</p> <p>Vibrations contactor open - 2 GN conforming to IEC 60068-2-6</p> <p>Vibrations contactor closed - 4 gn conforming to IEC 60068-2-6</p> |
|------------------------------|---|

| | |
|--------------------------------|------------------------------|
| IP degree of protection | IP54 conforming to IEC 60529 |
|--------------------------------|------------------------------|

| | |
|-----------------------------|----|
| Protective treatment | TC |
|-----------------------------|----|

| | |
|------------------------|------------------------------------|
| Fire resistance | 960 °C conforming to IEC 60695-2-1 |
|------------------------|------------------------------------|

| | |
|---------------------------|--------|
| Operating altitude | 2000 m |
|---------------------------|--------|

| | |
|------------------|---|
| Standards | <p>IEC 60439-1</p> <p>IEC 60947-1</p> <p>EN 60439-1</p> <p>EN 60204-1</p> <p>EN 60947-1</p> <p>UL 508</p> <p>IEC 60204-1</p> <p>CSA C22.2 No 14</p> |
|------------------|---|

| | |
|-----------------|-------------------------|
| Material | Steel - white: RAL 9001 |
|-----------------|-------------------------|

| | |
|--|--------------------------------------|
| Ambient air temperature for operation | -5...40 °C conforming to IEC 61439-1 |
|--|--------------------------------------|

| | |
|--|---------------------------------------|
| Ambient air temperature for storage | -40...80 °C conforming to IEC 61439-1 |
|--|---------------------------------------|

Contractual warranty

| | |
|-----------------------------|----|
| Warranty (in months) | 18 |
|-----------------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No