

Product datasheet

Specifications



earth leakage protection Domae - 2P - 25 A - 220...240 V - 30 mA

DOM16790

⚠ Discontinued on: 30 Mar 2022

⚠ Discontinued

Main

Range of product	Domae
Product or component type	Earth leakage protection
Poles description	2P
[In] rated current	25 A
Network type	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous

Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	220...240 V
Control type	Toggle
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	4
Colour	Grey

Environment

Standards	SNI 04-6507.1 IEC 60898-1
Product certifications	SNI

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.8 cm
Package 1 Width	3.6 cm
Package 1 Length	8.1 cm
Package 1 Weight	0.218 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

Use Better

Materials and Packaging	
SCIP Number	2c7837a4-39fc-4abc-96ed-2ef14f8f87c7

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
End of life manual availability	No need of specific recycling operations