

# Product data sheet

Specifications



## specific contactor coil - TeSys F - 19..21 V DC - low consumption

LX9FL910

⚠ Discontinued

### Main

Range	TeSys
Product or Component Type	Specific contactor coil
Device short name	LX9FL
Range compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F630
Control circuit type	AC 40...400 Hz low consumption DC low consumption
[Uc] control circuit voltage	19...21 V DC
Operating time	60 ms opening 20 ms closing
Mechanical durability	5 Mcycles
Maximum operating rate	1800 cyc/h 158 °F (70 °C)

### Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Operational 0.85...1.1 Uc 131 °F (55 °C) Drop-out 0.3...0.5 Uc 131 °F (55 °C)
Inrush power in W	733 W 68 °F (20 °C)
Hold-in power consumption in W	48 W 68 °F (20 °C)
Heat dissipation	22.8...27.8 W

### Environment

Ambient Air Temperature for Operation	23...131 °F (-5...55 °C)
Net Weight	3.20 lb(US) (1.45 kg)

### Ordering and shipping details

Category	22341-CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	3389118112049
Returnability	No

### Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Nbr. of units in pkg. 1

## Contractual warranty

---

Warranty (in months) 18



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Longer



### Lifetime extension

[Repair](#)

[No](#)