


Product datasheet

Specifications



TeSys Deca - auxiliary contact - 1 NO + 1 NC

GK2AX50

⚠ Discontinued on: 10 Dec 2021

⚠ Discontinued

Main

Range	TeSys
Device short name	GK2AX
Product or component type	Auxiliary contact block
Product compatibility	GK3EF
Mounting location	Right side
Pole contact composition	1 NO + 1 NC
Quantity per set	Set of 10

Complementary

[Ui] rated insulation voltage	500 V conforming to IEC 60947-1
[Ue] rated operational voltage	500 V
[Ith] conventional free air thermal current	6 A
Protection type	GB2CB... circuit breaker GG fuse 6 A
Rated operational power in VA	360 VA at 48 V AC-15 - electrical durability: 20000 cycles at 6 A 500 VA at 110...127 V AC-15 - electrical durability: 20000 cycles at 4.5 A 800 VA at 220...240 V AC-15 - electrical durability: 20000 cycles at 3.5 A 850 VA at 380...415 V AC-15 - electrical durability: 20000 cycles at 2.2 A 700 VA at 440 V AC-15 - electrical durability: 20000 cycles at 1.5 A 700 VA at 500 V AC-15 - electrical durability: 20000 cycles at 1.5 A
Rated operational power in W	180 W at 24 V DC-13 - electrical durability: 1000 cycles 240 W at 48 V DC-13 - electrical durability: 1000 cycles 180 W at 60 V DC-13 - electrical durability: 1000 cycles 140 W at 110 V DC-13 - electrical durability: 1000 cycles 120 W at 220 V DC-13 - electrical durability: 1000 cycles
Height	80 mm
Width	8.8 mm
Depth	105 mm
Net weight	0.031 kg

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	1.4 cm
Package 1 Width	8.0 cm
Package 1 Length	8.0 cm
Package 1 Weight	40.0 g
Unit Type of Package 2	S01
Number of Units in Package 2	30
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	1.425 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
SCIP Number	04104e70-ba29-493c-b2cc-b5837d1f902b
EU RoHS Directive	Compliant By Exemption

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
End of life manual availability	End of Life Information
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Connections and Schema

GK2AX50

