

TeSys Control

K Contactors - Auxiliary contacts blocks

Product references



LA1KN22



LA1KN223



LA1KN407

Instantaneous auxiliary contact blocks

Recommended for standard applications. Clip-on front mounting, 1 block per contactor

Connection	For use on contactors	Composition		Reference
				
Screw clamp terminals	All products with screw clamp terminals	2	—	LA1KN20
		—	2	LA1KN02
		1	1	LA1KN11
	All products with screw clamp terminals except low consumption	4	—	LA1KN40
		3	1	LA1KN31
		2	2	LA1KN22
		1	3	LA1KN13
		—	4	LA1KN04
Spring terminals	All products with spring terminals	2	—	LA1KN203
		—	2	LA1KN023
		1	1	LA1KN113
	All products with spring terminals except low consumption	4	—	LA1KN403
		3	1	LA1KN313
		2	2	LA1KN223
		1	3	LA1KN133
		—	4	LA1KN043
Faston connectors, 1 x 6.35 or 2 x 2.8	All products with Faston connectors	2	—	LA1KN207
	All products with Faston connectors except low consumption	4	—	LA1KN407
		3	1	LA1KN317

With terminal referencing to standard EN 50012. Clip-on front mounting, 1 block per contactor

Screw clamp terminals with referencing conforming to standard EN 50012	All 3-pole + N/O products with screw clamp terminals except LP4 and LP5K12	—	2	LA1KN02M
		1	1	LA1KN11M
	All 3-pole + N/O products with screw clamp terminals except LP4 or LP5K06, K09 and K12	3	1	LA1KN31M
		2	2	LA1KN22M

Electronic time delay auxiliary contact blocks

Relay output with common point changeover contact, ~ or — 240 V, 2 A maximum.

Control voltage 0.85...1.1 Uc.

Maximum switching capacity 250 VA or 150 W.

Operating temperature -10...+60 °C.

Reset time: 1.5 s during the time delay period, 0.5 s after the time delay period.

Clip-on front mounting, 1 block per contactor

Voltage	Type	Timing range	Composition	Reference
				
V		s		
~ or — 24...48	On-delay	1...30	1	LA2KT2E
~ 110...240	On-delay	1...30	1	LA2KT2U