

Product datasheet

Specifications



AS-Interface - modular - extended A/B - 4 I - IP20

ASI20MT4IE

⚠ Discontinued on: 23 Jan 2021

⚠ Discontinued

Main

Range of product	Advantys
Product or component type	Modular interface
Addressing	Extended A/B
Number of addresses	0...62
Discrete input number	4
Supply	Sensor: via AS-Interface line
Actuator sensor interface profile [AS-i]	S0.A.7.0

Complementary

Range compatibility	AS-Interface cabling system
AS-Interface compatibility	V2.1
[Us] rated supply voltage	26.5...31.6 V DC for AS-Interface line
Maximum sensor supply current	170 mA
Current consumption	<= 50 mA on inputs/outputs on and sensor not energised for AS-Interface line 15 mA on no load for AS-Interface line
Input compatibility	2 or 3-wire PNP conforming to IEC 61131-2 Type 2
Voltage state 1 guaranteed	> 11 V for sensor side
Current state 1 guaranteed	>= 6 mA (sensor side)
Voltage state 0 guaranteed	< 5 V for sensor side
Current state 0 guaranteed	<= 2 mA (sensor side)
Switching time	1 ms at OFF to ON for actuator side 1 ms at ON to OFF for actuator side
Output fallback position	State 0 if watchdog tripped
Parameter bits	Not used
Overvoltage category	II conforming to EN/IEC 60664-1
Electrical connection	Removable terminal block for AS-Interface line Removable terminal block for sensor side
Fixing mode	By 2 screws diameter: 3 mm on panel Clip-on on 35 mm symmetrical DIN rail, operating position: horizontal
Housing material	Polycarbonate
Flame retardance	V0 conforming to UL 94

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Local signalling	1 LED (green) for AS-Interface power on 1 LED (green) for auxiliary supply on 1 LED (red) for no data exchange on AS-Interface (on steady), peripheral fault (flashing) 4 LEDs (yellow) for input status
Net weight	0.09 kg

Environment

Product certifications	CSA AS-Interface No 52501 UL
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...85 °C
IP degree of protection	IP20 conforming to EN/IEC 60529
Shock resistance	15 gn for 11 ms conforming to EN/IEC 60068-2-27
Vibration resistance	+/-1 mm (f = 2...13.2 Hz) 1 gn (f = 13.2...100 Hz)
Resistance to electrostatic discharge	6 kV conforming to EN/IEC 61000-4-2
Resistance to radiated fields	10 V/m conforming to EN/IEC 61000-4-3
Resistance to fast transients	2 kV conforming to EN/IEC 61000-4-4
Pollution degree	2 conforming to EN/IEC 60664-1

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No