

Loadcentres

SPA panel and Mini Panel/Enclosed Breaker

Selection

Selection and Ordering Data



 W0408ML1125  2-POLE GFCI	SPA panel package, 3R enclosure 120/240V 1 Phase 3 Wire								
	Number of Circuits	Package Catalogue Number	Main Amps.	GFCI Included	Enclosure Dimensions - Inches (mm)			Hubs (sold seperately)	
					H	W	D	Conduit Size (")	Catalogue Number
	4/8	W0408ML1125-20	125	QF220	12 ^{1/4} (312)	6 (153)	4 ^{1/4} (108)	Cover 3/4 1 1 ^{1/4} 1 ^{1/2} 2 2 ^{1/2}	ECHS000 ECHS075 ECHS100 ECHS125 ECHS150 ECHS200 ECHS250
		W0408ML1125-30		QF230					
		W0408ML1125-40		QF240					
		W0408ML1125-50		QF250					
W0408ML1125-60		QF260							
Each package also includes a 4-point ground bar and French instructions.									

Circuit Breaker Enclosures for Service Entrance and Commercial Use							
EEMAC 1 Enclosure (Indoor) 1 phase 3 wire 240V AC Max.							
Breaker Range	Catalogue Number	Main Amps.	Number of Poles	Dimensions - Inches (mm)			Lug Data
				H	W	D	
15-60A	EQS260* ^①	60	1,2	7 ^{3/4} (197)	5 (127)	2 ^{3/4}	14-4 (70)
15-125A	EQS2125* ^①	125	1,2	13 (330)	6 ^{5/8} (168)	3 ^{3/8}	14-2/0 (86)
*Does not accept quad type breaker.							

EEMAC 3R Weatherproof Enclosure, 1 phase 3 wire 240V AC Max.							
Full Module Circuits	Catalogue Number	Main Amps.	Dimensions - Inches (mm)			Weight lbs.	Hub ^② Type
			H	W	D		
3	WEQ60-4 ^③	60	10 ^{1/4} (260)	9 ^{1/2} (241)	5 ^{5/8} (143)	8	HR
2/4	W0204ML1060 ^③	60	8 (204)	5 (127)	4 ^{1/4} (108)	4	HA
4/8	W0408ML1125 ^③	125	12 ^{1/4} (312)	6 (153)	4 ^{1/4} (108)	7	HS

Key Features:
Outdoor EEMAC 3R enclosure

- Accepts plug-in Q type breakers
- One piece bus bar construction
- Combination trim flush/surface

Remark:

① The panels will not accommodate a 2 pole ground fault breaker (GFCI) or breaker with shunt trip.

② Hubs sold seperately

③ Not to be used as service entrance.

Hubs

Catalogue Number	Conduit size (")	Catalogue Number	Conduit size (")
ECHA075	3/4	ECHS075	3/4
ECHA100	1	ECHS100	1
ECHA125	1 1/4	ECHS125	1 1/4
ECHR075	3/4	ECHS150	1 1/2
ECHR100	1	ECHS200	2
ECHR125	1 1/4	ECHS250	2.5
ECHR150	1 1/2		