


# Product datasheet

Specifications



Communicating motor mechanism (MCH), drawout ComPacT NS630b/NS1600, 200/250VDC, MX coil, ready to close contact

LV533840

⚠ Discontinued on: 31 Mar 2021

⚠ Discontinued

## Main

Product or component type	Motor mechanism with external connector
Device application	Automatic spring charging
Range compatibility	ComPact NS630b...1600 circuit breaker
Control type	Communicating
[Uc] control circuit voltage	200...250 V DC
circuit breaker mounting mode	Drawout
circuit breaker frame rated current	1600 A 800 A 1000 A 630 A 1250 A

## Complementary

Control signal type	Maintained Impulse
circuit breaker response time	< 600 ms open < 80 ms closed
Maximum power consumption in VA	500 VA
Provided equipment	Auxiliary contact Voltage release

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	8.0 cm
Package 1 Length	10.5 cm
Package 1 Weight	410.0 g

## Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	3 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.1 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.9 kg CO2 eq.

### Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	7c479875-b986-4ae2-a2e9-f5f369faf4e7
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

### Use Longer




### Lifetime extension

Repair	No
--------	----

### Use Again



### Repack and remanufacture

Recyclability potential, in %	73
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins