

Product data sheet

Specifications



pre-wired connector with other cable end open for stepper motor drive - 3 m

VW3L3M01R30

Main

Product or component type	Pre-wired connector with other cable end open
Accessory / separate part type	Cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	For stepper motor drive
Cable length	9.8 ft (3 m)

Complementary

Range compatibility	Lexium SD2
Product compatibility	SD218AU50C SD215DU50C SD218PU50C
Electrical connection	1 connector wire crimp, 4 pins motor interface Cable end open
Net weight	1.376 lb(US) (0.624 kg)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.8 in (7.0 cm)
Package 1 Width	12.2 in (31.0 cm)
Package 1 Length	13.0 in (33.0 cm)
Package 1 Weight	22.01 oz (624.0 g)

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	97 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	3 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	93 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No