



SIRIUS soft starter 200-480 V 25 A, 110-250 V AC spring-type terminals

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| product brand name            | SIRIUS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| product category              | Hybrid switching devices                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| product designation           | Soft starter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| product type designation      | 3RW55                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| manufacturer's article number | <ul style="list-style-type: none"> <li>• of high feature HMI module usable <a href="#">3RW5980-0HF00</a></li> <li>• of communication module PROFINET standard usable <a href="#">3RW5980-0CS00</a></li> <li>• of communication module PROFINET high-feature usable <a href="#">3RW5950-0CH00</a></li> <li>• of communication module PROFIBUS usable <a href="#">3RW5980-0CP00</a></li> <li>• of communication module Modbus TCP usable <a href="#">3RW5980-0CT00</a></li> <li>• of communication module Modbus RTU usable <a href="#">3RW5980-0CR00</a></li> <li>• of communication module Ethernet/IP <a href="#">3RW5980-0CE00</a></li> <li>• of circuit breaker usable at 400 V <a href="#">3RV2032-4EA10; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 500 V <a href="#">3RV2032-4EA10; Type of coordination 1, Iq = 15 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 400 V at inside-delta circuit <a href="#">3RV2032-4VA10; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 500 V at inside-delta circuit <a href="#">3RV2032-4VA10; Type of coordination 1, Iq = 15 kA, CLASS 10</a></li> <li>• of the gG fuse usable up to 690 V <a href="#">3NA3822-6; Type of coordination 1, Iq = 65 kA</a></li> <li>• of the gG fuse usable at inside-delta circuit up to 500 V <a href="#">3NA3822-6; Type of coordination 1, Iq = 65 kA</a></li> <li>• of full range R fuse link for semiconductor protection usable up to 690 V <a href="#">3NE1817-0; Type of coordination 2, Iq = 65 kA</a></li> <li>• of back-up R fuse link for semiconductor protection usable up to 690 V <a href="#">3NE8021-1; Type of coordination 2, Iq = 65 kA</a></li> </ul> |

| General technical data                |                                                                |
|---------------------------------------|----------------------------------------------------------------|
| starting voltage [%]                  | 20 ... 100 %                                                   |
| stopping voltage [%]                  | 50 %; non-adjustable                                           |
| start-up ramp time of soft starter    | 0 ... 360 s                                                    |
| ramp-down time of soft starter        | 0 ... 360 s                                                    |
| start torque [%]                      | 10 ... 100 %                                                   |
| stopping torque [%]                   | 10 ... 100 %                                                   |
| torque limitation [%]                 | 20 ... 200 %                                                   |
| current limiting value [%] adjustable | 125 ... 800 %                                                  |
| breakaway voltage [%] adjustable      | 40 ... 100 %                                                   |
| breakaway time adjustable             | 0 ... 2 s                                                      |
| number of parameter sets              | 3                                                              |
| accuracy class                        | 5 (based on IEC 61557-12)                                      |
| certificate of suitability            | <ul style="list-style-type: none"> <li>• CE marking</li> </ul> |

|                                                              |                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • UL approval                                                | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • CSA approval                                               | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>product component</b>                                     |                                                                                                                                                                                                                                                                                                                                                                                                      |
| • HMI-High Feature                                           | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • is supported HMI-High Feature                              | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>product feature integrated bypass contact system</b>      | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>number of controlled phases</b>                           | 3                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>current unbalance limiting value [%]</b>                  | 10 ... 60 %                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>ground-fault monitoring limiting value [%]</b>            | 10 ... 95 %                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>buffering time in the event of power failure</b>          |                                                                                                                                                                                                                                                                                                                                                                                                      |
| • for main current circuit                                   | 100 ms                                                                                                                                                                                                                                                                                                                                                                                               |
| • for control circuit                                        | 100 ms                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>idle time adjustable</b>                                  | 0 ... 255 s                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>insulation voltage rated value</b>                        | 480 V                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>degree of pollution</b>                                   | 3, acc. to IEC 60947-4-2                                                                                                                                                                                                                                                                                                                                                                             |
| <b>impulse voltage rated value</b>                           | 6 kV                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>blocking voltage of the thyristor maximum</b>             | 1 600 V                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>service factor</b>                                        | 1.15                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>surge voltage resistance rated value</b>                  | 6 kV                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>maximum permissible voltage for protective separation</b> |                                                                                                                                                                                                                                                                                                                                                                                                      |
| • between main and auxiliary circuit                         | 480 V; does not apply for thermistor connection                                                                                                                                                                                                                                                                                                                                                      |
| <b>shock resistance</b>                                      | 15 g / 11 ms, from 6 g / 11 ms with potential contact lifting                                                                                                                                                                                                                                                                                                                                        |
| <b>vibration resistance</b>                                  | 15 mm up to 6 Hz; 2 g up to 500 Hz                                                                                                                                                                                                                                                                                                                                                                   |
| <b>recovery time after overload trip adjustable</b>          | 60 ... 1 800 s                                                                                                                                                                                                                                                                                                                                                                                       |
| utilization category according to IEC 60947-4-2              | AC 53a                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>reference code according to IEC 81346-2</b>               | Q                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Substance Prohibitance (day/month/year)</b>               | 02/15/2018                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>SVHC substance name</b>                                   | Lead CAS-No. 7439-92-1<br>Lead monoxide (lead oxide) CAS-No. 1317-36-8<br>2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5<br>Melamine CAS-No. 108-78-1<br>6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol CAS-No. 119-47-1<br>Dibutylbis(pentane-2,4-dionato-O,O')tin CAS-No. 22673-19-4<br>Diboron trioxide CAS-No. 1303-86-2<br>Lead titanium trioxide CAS-No. 12060-00-3 |
| <b>Net Weight</b>                                            | 3.399 kg                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>product function</b>                                      |                                                                                                                                                                                                                                                                                                                                                                                                      |
| • ramp-up (soft starting)                                    | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • soft stopping                                              | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • breakaway pulse                                            | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • adjustable current limitation                              | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • creep speed in both directions of rotation                 | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • pump stop                                                  | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • DC braking                                                 | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • motor heating                                              | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • min/max pointer                                            | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • trace function                                             | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • intrinsic device protection                                | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • motor overload protection                                  | Yes; Full motor protection (thermistor motor protection and electronic motor overload protection) / When using the motor overload protection according to ATEX, an upstream contactor is required in inside-delta circuit.                                                                                                                                                                           |
| • evaluation of thermistor motor protection                  | Yes; Type A PTC or Klixon / Thermoclick                                                                                                                                                                                                                                                                                                                                                              |
| • inside-delta circuit                                       | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • auto-RESET                                                 | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • manual RESET                                               | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • remote reset                                               | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • communication function                                     | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • operating measured value display                           | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • event list                                                 | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • error logbook                                              | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |
| • via software parameterizable                               | Yes                                                                                                                                                                                                                                                                                                                                                                                                  |

- via software configurable

- screw terminal

- spring-loaded terminal

- **PROFInergy**

- **firmware update**

- **removable terminal for control circuit**

- voltage ramp

- torque control

- combined braking

- analog output

- programmable control inputs/outputs

- condition monitoring

- automatic parameterisation

- application wizards

- alternative stopping mode

- emergency operation mode

- reversing operation

- soft starting at heavy starting conditions

Yes

No

Yes

Yes; in connection with the PROFINET Standard and PROFINET High-Feature communication modules

Yes

Yes

Yes

Yes

Yes

Yes; 4 ... 20 mA (default) / 0 ... 10 V

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes

## Power Electronics

### operational current

- at 40 °C rated value

25 A

- at 40 °C rated value minimum

5 A

- at 50 °C rated value

22.3 A

- at 60 °C rated value

19.6 A

### operational current at inside-delta circuit

- at 40 °C rated value

43.3 A

- at 50 °C rated value

39 A

- at 60 °C rated value

33.9 A

### operating voltage

- rated value

200 ... 480 V

- at inside-delta circuit rated value

200 ... 480 V

### relative negative tolerance of the operating voltage

-15 %

### relative positive tolerance of the operating voltage

10 %

### relative negative tolerance of the operating voltage at inside-delta circuit

-15 %

### relative positive tolerance of the operating voltage at inside-delta circuit

10 %

### operating power for 3-phase motors

- at 230 V at 40 °C rated value

5.5 kW

- at 230 V at inside-delta circuit at 40 °C rated value

11 kW

- at 400 V at 40 °C rated value

11 kW

- at 400 V at inside-delta circuit at 40 °C rated value

18.5 kW

### Operating frequency 1 rated value

50 Hz

### Operating frequency 2 rated value

60 Hz

### relative negative tolerance of the operating frequency

-10 %

### relative positive tolerance of the operating frequency

10 %

### minimum load [%]

10 %; Relative to set le

### power loss [W] for rated value of the current at AC

- at 40 °C after startup

8 W

- at 50 °C after startup

7 W

- at 60 °C after startup

6 W

### power loss [W] at AC at current limitation 350 %

- at 40 °C during startup

364 W

- at 50 °C during startup

309 W

- at 60 °C during startup

262 W

### type of the motor protection

Electronic, tripping in the event of thermal overload of the motor

## Control circuit/ Control

### type of voltage of the control supply voltage

AC

### control supply voltage at AC

|                                                                                 |                                                                                                                                                                                |
|---------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • at 50 Hz                                                                      | 110 ... 250 V                                                                                                                                                                  |
| • at 60 Hz                                                                      | 110 ... 250 V                                                                                                                                                                  |
| <b>relative negative tolerance of the control supply voltage at AC at 50 Hz</b> | -15 %                                                                                                                                                                          |
| <b>relative positive tolerance of the control supply voltage at AC at 50 Hz</b> | 10 %                                                                                                                                                                           |
| <b>relative negative tolerance of the control supply voltage at AC at 60 Hz</b> | -15 %                                                                                                                                                                          |
| <b>relative positive tolerance of the control supply voltage at AC at 60 Hz</b> | 10 %                                                                                                                                                                           |
| <b>control supply voltage frequency</b>                                         | 50 ... 60 Hz                                                                                                                                                                   |
| <b>relative negative tolerance of the control supply voltage frequency</b>      | -10 %                                                                                                                                                                          |
| <b>relative positive tolerance of the control supply voltage frequency</b>      | 10 %                                                                                                                                                                           |
| <b>control supply current in standby mode rated value</b>                       | 100 mA                                                                                                                                                                         |
| <b>holding current in bypass operation rated value</b>                          | 165 mA                                                                                                                                                                         |
| <b>inrush current by closing the bypass contacts maximum</b>                    | 0.2 A                                                                                                                                                                          |
| inrush current peak at application of control supply voltage maximum            | 43 A                                                                                                                                                                           |
| duration of inrush current peak at application of control supply voltage        | 1.6 ms                                                                                                                                                                         |
| <b>design of the overvoltage protection</b>                                     | Varistor                                                                                                                                                                       |
| <b>design of short-circuit protection for control circuit</b>                   | 4 A gG fuse (Icu=1 kA), 6 A quick-acting fuse (Icu=1 kA), C1 miniature circuit breaker (Icu= 600 A), C6 miniature circuit breaker (Icu= 300 A); Is not part of scope of supply |

#### Inputs/ Outputs

|                                                        |                                                           |
|--------------------------------------------------------|-----------------------------------------------------------|
| <b>number of digital inputs</b>                        | 4                                                         |
| • parameterizable                                      | 4                                                         |
| • <b>number of digital outputs</b>                     | 4                                                         |
| • number of digital outputs parameterizable            | 3                                                         |
| • number of digital outputs not parameterizable        | 1                                                         |
| <b>digital output version</b>                          | 3 normally-open contacts (NO) / 1 changeover contact (CO) |
| <b>number of analog outputs</b>                        | 1                                                         |
| <b>switching capacity current of the relay outputs</b> |                                                           |
| • at AC-15 at 250 V rated value                        | 3 A                                                       |
| • at DC-13 at 24 V rated value                         | 1 A                                                       |

#### Installation/ mounting/ dimensions

|                                             |                                                                            |
|---------------------------------------------|----------------------------------------------------------------------------|
| <b>mounting position</b>                    | Vertical (can be rotated +/- 90° and tilted forward or backward +/- 22.5°) |
| <b>fastening method</b>                     | screw fixing                                                               |
| <b>height</b>                               | 275 mm                                                                     |
| <b>width</b>                                | 170 mm                                                                     |
| <b>depth</b>                                | 152 mm                                                                     |
| required spacing with side-by-side mounting |                                                                            |
| • forwards                                  | 10 mm                                                                      |
| • backwards                                 | 0 mm                                                                       |
| • upwards                                   | 100 mm                                                                     |
| • downwards                                 | 75 mm                                                                      |
| • at the side                               | 5 mm                                                                       |
| <b>weight without packaging</b>             | 2.3 kg                                                                     |

#### Connections/ Terminals

|                                                     |                                           |
|-----------------------------------------------------|-------------------------------------------|
| <b>type of electrical connection</b>                |                                           |
| • for main current circuit                          | screw-type terminals                      |
| • for control circuit                               | spring-loaded terminals                   |
| <b>wire length for thermistor connection</b>        |                                           |
| • with conductor cross-section = 0.5 mm² maximum    | 50 m                                      |
| • with conductor cross-section = 1.5 mm² maximum    | 150 m                                     |
| • with conductor cross-section = 2.5 mm² maximum    | 250 m                                     |
| <b>type of connectable conductor cross-sections</b> |                                           |
| • for main contacts                                 |                                           |
| — solid                                             | 2x (1.0 ... 2.5 mm²), 2x (2.5 ... 10 mm²) |

|                                                                                      |                                                                                                                         |
|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| — finely stranded with core end processing                                           | 2x (1.0 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6.0 mm <sup>2</sup> )                                                    |
| • for AWG cables for main current circuit solid                                      | 2x (16 ... 12), 2x (14 ... 8)                                                                                           |
| <b>type of connectable conductor cross-sections</b>                                  |                                                                                                                         |
| • for control circuit solid                                                          | 2x (0.25 ... 1.5 mm <sup>2</sup> )                                                                                      |
| • for control circuit finely stranded with core end processing                       | 2x (0.25 ... 1.5 mm <sup>2</sup> )                                                                                      |
| • for AWG cables for control circuit solid                                           | 2x (24 ... 16)                                                                                                          |
| • for AWG cables for control circuit finely stranded with core end processing        | 2x (24 ... 16)                                                                                                          |
| <b>wire length</b>                                                                   |                                                                                                                         |
| • between soft starter and motor maximum                                             | 800 m                                                                                                                   |
| • at the digital inputs at DC maximum                                                | 1 000 m                                                                                                                 |
| <b>tightening torque</b>                                                             |                                                                                                                         |
| • for main contacts with screw-type terminals                                        | 2 ... 2.5 N·m                                                                                                           |
| • for auxiliary and control contacts with screw-type terminals                       | 0.8 ... 1.2 N·m                                                                                                         |
| <b>tightening torque [lbf·in]</b>                                                    |                                                                                                                         |
| • for main contacts with screw-type terminals                                        | 18 ... 22 lbf·in                                                                                                        |
| • for auxiliary and control contacts with screw-type terminals                       | 7 ... 10.3 lbf·in                                                                                                       |
| <b>Ambient conditions</b>                                                            |                                                                                                                         |
| installation altitude at height above sea level maximum                              | 5 000 m                                                                                                                 |
| <b>ambient temperature</b>                                                           |                                                                                                                         |
| • during operation                                                                   | -25 ... +60 °C; Please observe derating at temperatures of 40 °C or above                                               |
| • during storage and transport                                                       | -40 ... +80 °C                                                                                                          |
| <b>environmental category</b>                                                        |                                                                                                                         |
| • during operation according to IEC 60721                                            | 3K6 (no ice formation, only occasional condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6 |
| • during storage according to IEC 60721                                              | 1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4                 |
| • during transport according to IEC 60721                                            | 2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m)                                                                             |
| <b>Electromagnetic compatibility</b>                                                 |                                                                                                                         |
| <b>EMC emitted interference</b>                                                      | acc. to IEC 60947-4-2: Class A, Class B on request                                                                      |
| <b>Communication/ Protocol</b>                                                       |                                                                                                                         |
| <b>communication module is supported</b>                                             |                                                                                                                         |
| • PROFINET standard                                                                  | Yes                                                                                                                     |
| • PROFINET high-feature                                                              | Yes                                                                                                                     |
| • EtherNet/IP                                                                        | Yes                                                                                                                     |
| • Modbus RTU                                                                         | Yes                                                                                                                     |
| • Modbus TCP                                                                         | Yes                                                                                                                     |
| • PROFIBUS                                                                           | Yes                                                                                                                     |
| <b>UL/CSA ratings</b>                                                                |                                                                                                                         |
| <b>manufacturer's article number</b>                                                 |                                                                                                                         |
| • <b>of circuit breaker usable for Standard Faults</b>                               |                                                                                                                         |
| — at 460/480 V according to UL                                                       | Siemens type: 3RV2742, max. 70 A or 3VA51, max. 80 A; I <sub>q</sub> = 5 kA                                             |
| — 60/480 V according to UL                                                           | Siemens type: 3RV2742, max. 40 A or 3VA51, max. 60 A; I <sub>q</sub> max = 65 kA                                        |
| — at 460/480 V at inside-delta circuit according to UL                               | Siemens type: 3RV2742, max. 70 A or 3VA51, max. 80 A; I <sub>q</sub> = 5 kA                                             |
| — 60/480 V at inside-delta circuit according to UL                                   | Siemens type: 3VA51, max. 60 A; I <sub>q</sub> max = 65 kA                                                              |
| — at 575/600 V according to UL                                                       | Siemens type: 3RV2742, max. 70 A or 3VA51, max. 80 A; I <sub>q</sub> = 5 kA                                             |
| — 75/600 V at inside-delta circuit according to UL                                   | Siemens type: 3VA51, max. 60 A; I <sub>q</sub> max = 65 kA                                                              |
| — at 575/600 V at inside-delta circuit according to UL                               | Siemens type: 3RV2742, max. 70 A or 3VA51, max. 80 A; I <sub>q</sub> = 5 kA                                             |
| • <b>of the fuse</b>                                                                 |                                                                                                                         |
| — usable for Standard Faults up to 575/600 V according to UL                         | Type: Class RK5 / K5, max. 100 A; I <sub>q</sub> = 5 kA                                                                 |
| — usable for High Faults up to 575/600 V according to UL                             | Type: Class J / L, max. 100 A; I <sub>q</sub> = 100 kA                                                                  |
| — usable for Standard Faults at inside-delta circuit up to 575/600 V according to UL | Type: Class RK5 / K5, max. 100 A; I <sub>q</sub> = 5 kA                                                                 |
| — usable for High Faults at inside-delta circuit up to 575/600 V according to UL     | Type: Class J / L, max. 100 A; I <sub>q</sub> = 100 kA                                                                  |
| <b>operating power [hp] for 3-phase motors</b>                                       |                                                                                                                         |
| • at 200/208 V at 50 °C rated value                                                  | 5 hp                                                                                                                    |

|                                                                                                                                                                                                                                                                                                                                                   |                                                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 220/230 V at 50 °C rated value</li> <li>• at 460/480 V at 50 °C rated value</li> <li>• at 200/208 V at inside-delta circuit at 50 °C rated value</li> <li>• at 220/230 V at inside-delta circuit at 50 °C rated value</li> <li>• at 460/480 V at inside-delta circuit at 50 °C rated value</li> </ul> | 7.5 hp<br>15 hp<br>10 hp<br>10 hp<br>25 hp       |
| <b>contact rating of auxiliary contacts according to UL</b>                                                                                                                                                                                                                                                                                       | R300-B300                                        |
| <b>Electrical Safety</b>                                                                                                                                                                                                                                                                                                                          |                                                  |
| <b>protection class IP on the front according to IEC 60529</b>                                                                                                                                                                                                                                                                                    | IP20                                             |
| <b>touch protection on the front according to IEC 60529</b>                                                                                                                                                                                                                                                                                       | finger-safe, for vertical contact from the front |

#### ATEX

|                                                                                                                                                               |                                                                                              |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| <b>Safety Integrity Level (SIL) according to IEC 61508 relating to ATEX</b>                                                                                   | SIL 1                                                                                        |
| <b>PFHD with high demand rate according to IEC 61508 relating to ATEX</b>                                                                                     | 5E-7 1/h                                                                                     |
| <b>PFDavg with low demand rate according to IEC 61508 relating to ATEX</b>                                                                                    | 0.008                                                                                        |
| <b>hardware fault tolerance according to IEC 61508 relating to ATEX</b>                                                                                       | 0                                                                                            |
| <b>T1 value for proof test interval or service life according to IEC 61508 relating to ATEX</b>                                                               | 3 a                                                                                          |
| <b>certificate of suitability</b> <ul style="list-style-type: none"> <li>• ATEX</li> <li>• IECEx</li> <li>• according to ATEX directive 2014/34/EU</li> </ul> | Yes<br>Yes<br>BVS 18 ATEX F 003 X                                                            |
| <b>type of protection according to ATEX directive 2014/34/EU</b>                                                                                              | II (2)G [Ex eb Gb] [Ex db Gb] [Ex pxb Gb], II (2)D [Ex tb Db] [Ex pxb Db], I (M2) [Ex db Mb] |

#### Approvals Certificates

|                                                                                                                                                                                                                                                                                                                                                                |                                                     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| <b>Environmental Product Declaration</b>                                                                                                                                                                                                                                                                                                                       |                                                     |
| <ul style="list-style-type: none"> <li>• global warming potential [CO2 eq] / during manufacturing</li> <li>• global warming potential [CO2 eq] / during sales</li> <li>• global warming potential [CO2 eq] / during operation</li> <li>• global warming potential [CO2 eq] / after end of life</li> <li>• global warming potential [CO2 eq] / total</li> </ul> | 50.8 kg<br>0.827 kg<br>240 kg<br>-7.11 kg<br>285 kg |
| <b>Environment</b>                                                                                                                                                                                                                                                                                                                                             | <b>General Product Approval</b>                     |

[Environmental Confirmations](#)



|                                 |            |                                       |
|---------------------------------|------------|---------------------------------------|
| <b>General Product Approval</b> | <b>EMV</b> | <b>For use in hazardous locations</b> |
|                                 |            |                                       |

|                                                    |                             |
|----------------------------------------------------|-----------------------------|
| <b>Test Certificates</b>                           | <b>Maritime application</b> |
| <a href="#">Type Test Certificates/Test Report</a> |                             |

|                              |                              |                                                                                     |
|------------------------------|------------------------------|-------------------------------------------------------------------------------------|
| other                        |                              |                                                                                     |
| <a href="#">Confirmation</a> | <a href="#">Confirmation</a> |  |

## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5515-3HA14>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5515-3HA14>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5515-3HA14&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5515-3HA14&lang=en)

### Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5515-3HA14>

### Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP='HAUPT'></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>)

### Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current


<https://support.industry.siemens.com/cs/ww/en/ps/3RW5515-3HA14/char>


### Characteristic: Installation altitude

[https://www.automation.siemens.com/bilddb/index.aspx?gridview=view2&objkey=G\\_NSB0\\_XX\\_01704&showdetail=true&view=Search](https://www.automation.siemens.com/bilddb/index.aspx?gridview=view2&objkey=G_NSB0_XX_01704&showdetail=true&view=Search)

### Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>





last modified:

9/5/2025



