


Product datasheet

Specifications

passive filter, Altivar, 10A, 400V, for variable speed drive



VW3A4602

⚠ Discontinued on: 5 Aug 2021

⚠ End-of-service on: 24 Nov 2021

⚠ Discontinued

Main

Product or component type	Passive filter
Product specific application	Reduction of current harmonics

Complementary

Range compatibility	Altivar 61 Altivar 71
[Us] rated supply voltage	400 V +/- 10 %
power supply frequency	50 Hz +/- 5 %
Quantity per drive	1 filter per drive for ATV61HU40N4 1 filter per drive for ATV61HU55N4 1 filter per drive for ATV61WU40N4 1 filter per drive for ATV61WU40N4C 1 filter per drive for ATV61WU55N4 1 filter per drive for ATV61WU55N4C 1 filter per drive for ATV71HU40N4 1 filter per drive for ATV71HU55N4 1 filter per drive for ATV71PU40N4Z 1 filter per drive for ATV71PU55N4Z 1 filter per drive for ATV71WU40N4 1 filter per drive for ATV71WU55N4
[In] rated current	10 A
Network number of phases	3 phases
THDI	10 % for ATV61WU40N4 motor: 4 kW/5 hp 10 % for ATV61WU40N4C motor: 4 kW/5 hp 10 % for ATV61WU55N4 motor: 5.5 kW/7.5 hp 10 % for ATV61WU55N4C motor: 5.5 kW/7.5 hp 16 % for ATV61HU40N4 motor: 4 kW/5 hp 16 % for ATV61HU55N4 motor: 5.5 kW/7.5 hp 16 % for ATV71HU40N4 motor: 4 kW/5 hp 16 % for ATV71HU55N4 motor: 5.5 kW/7.5 hp 16 % for ATV71PU40N4Z motor: 4 kW/5 hp 16 % for ATV71PU55N4Z motor: 5.5 kW/7.5 hp 16 % for ATV71WU40N4 motor: 4 kW/5 hp 16 % for ATV71WU55N4 motor: 5.5 kW/7.5 hp
Max current	1.5 x nominal current
Efficiency	98 %
Cos phi	1 (150 % of line current) 0.85 (75 % of line current) 0.99 (100 % of line current)
Electrical connection	terminal, connection capacity: 16 mm ²
Electrical insulation class	Class F
Net weight	19 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

IP degree of protection	IP20
-------------------------	------

Relative humidity	5...85 % without condensation
-------------------	-------------------------------

Ambient air temperature for operation	40...55 °C (with current derating 3 % per °C) 5...40 °C (without current derating)
---------------------------------------	---

Ambient air temperature for storage	-25...55 °C
-------------------------------------	-------------

Operating altitude	<= 1000 m without current derating > 1000...4000 m with current derating 5 % per 1000 m
--------------------	--

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer




Lifetime extension

Repair

No

Dimensions Drawings

Dimensions



Mounting and Clearance

Mounting Recommendations

Vertical Mounting Only

