

Product datasheet

Specifications



Remote transfer switch, WATSN, 250A, 4P, 400V, PC

NR02504

⚠ Discontinued on: 25 Sept 2023

⚠ Discontinued

Main

Range of product	WATSN
Device short name	WATSN250
Product or component type	Transfer switch
Device application	Remote control
Network type	AC
Network frequency	50/60 Hz
Mounting mode	Rack-mounted
Downside connection	Screwed
Upside connection	Screwed
Contact position indicator	Yes
Suitability for isolation	Yes

Complementary

Number of contact position	3
Control type	R
Mounting support	Plate
Transfer switch class	PC
Utilisation category	AC-33B
Locking options description	Padlock in OFF position
[Ie] rated operational current	250 A
[Ui] rated insulation voltage	800 V
[Uimp] rated impulse withstand voltage	8 kV
Mechanical interlocking	With mechanical interlocking
Mechanical durability	10000 cycles
Electrical durability	6000 cycles
[Ue] rated operational voltage	400 V AC 50/60 Hz
Rated conditional short-circuit current	NSX250H: Iq 70 kA NT1: Iq 100 kA
Height	290 mm
Width	430 mm
Depth	184 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net weight	14.3 kg
------------	---------

Environment

Product certifications	CCC CB CE
Standards	GB/T 14048.11 IEC 60947-6-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-35...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.4 cm
Package 1 Width	29.0 cm
Package 1 Length	43.0 cm
Package 1 Weight	14.3 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	485 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	91 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	363 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	29 kg CO2 eq.

Use Better



Materials and Packaging

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	90
End of life manual availability	End of Life Information
Take-back	No