

# Product datasheet

Specifications



## TeSys F magnetic latching contactor - 3P(3 NO) - 150 A - 110 V DC coil

CR1F150FZ7

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

### Main

Range	TeSys
Product name	TeSys F
Product or component type	Magnetic latching contactor
Device short name	CR1F
Device application	Control
Contactor application	Motor control Resistive load
Utilisation category	AC-1 AC-4 AC-3
Poles description	3P
power pole contact composition	3 NO
[Ue] rated operational voltage	1000 V AC 25...200 Hz
[Ie] rated operational current	150 A (at <40 °C) at ≤ 440 V AC AC-3 250 A (at <40 °C) at ≤ 440 V AC AC-1 138 A (at <40 °C) at ≤ 440 V AC AC-4
Motor power kW	75 kW at 400 V AC 50/60 Hz (AC-4)
Control circuit type	DC low consumption
[Uc] control circuit voltage	110 V DC
Irms rated making capacity	1700 A
Rated breaking capacity	1500 A at 220...440 V 1200 A at 500 V 450 A at 1000 V 1100 A at 660/690 V
[Icw] rated short-time withstand current	1200 A 40 °C - 1 s 1200 A 40 °C - 5 s 1200 A 40 °C - 10 s 700 A 40 °C - 30 s 600 A 40 °C - 1 min 450 A 40 °C - 3 min 350 A 40 °C - 10 min
Associated fuse rating	160 A aM at ≤ 440 V 250 A BS88 at ≤ 440 V 250 A gG at ≤ 440 V
Average impedance	0.45 mOhm - Ith 250 A 50 Hz
[Ui] rated insulation voltage	1000 V conforming to IEC 60158-1 1000 V conforming to IEC 60947-4 1000 V conforming to BS 775 1500 V conforming to VDE 0110 group C

<b>Power dissipation per pole</b>	6 W AC-3 18 W AC-1
<b>Connections - terminals</b>	Lugs-ring terminals 1 cable(s) 120 mm <sup>2</sup> Connector 1 cable(s) 120 mm <sup>2</sup> Bars 2 cable(s) - busbar cross section: 25 x 3 mm Power circuit: bolted connection
<b>Tightening torque</b>	18 N.m
<b>Operating time</b>	35...40 ms latching 50...100 ms unlatching
<b>Mechanical durability</b>	1 Mcycles
<b>Maximum operating rate</b>	120 cyc/h 40 °C

## Complementary

<b>Control circuit voltage limits</b>	Latching: 0.85...1.1 Uc Unlatching: 0.85...1.1 Uc
<b>average consumption</b>	500 W DC latching 15 W DC unlatching

## Environment

<b>Protective treatment</b>	TC
<b>Ambient air temperature for operation</b>	-15...70 °C
<b>Ambient air temperature for storage</b>	-60...80 °C
<b>Operating altitude</b>	3000 m without derating
<b>Height</b>	170 mm
<b>Width</b>	163.5 mm
<b>Depth</b>	171 mm
<b>Net weight</b>	3.5 kg

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	20 cm
<b>Package 1 Width</b>	20.5 cm
<b>Package 1 Length</b>	23 cm
<b>Package 1 Weight</b>	3.715 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

End of life manual availability

[End of Life Information](#)

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins