



Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Thermal-magnetic
Breaking capacity code	J
Accessory / separate part type	Auxiliary switch 2 NO + 2 NC
Product compatibility	Plug-in base not included

Complementary

Line Rated Current	250 A
Number of poles	3
Poles description	3P
Breaking capacity	20 kA 250 V DC 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC
System Voltage	250 V DC 600 V AC
Continuous current rating	80 %
Mounting mode	Plug-in
Electrical connection	Plug-in line Plug-in load
Magnetic hold current	1250 A
Magnetic tripping current	2500 A
Height	8 in
Width	4.12 in
Depth	12.72 in

Environment

product certifications	CCC CE CSA IEC UL listed
ambient air temperature for operation	104 °F (40 °C)

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0832 - Schneider Electric declaration of conformity	Compliant - since 0832 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
DINP, which is known to the State of California to cause cancer, and	DINP, which is known to the State of California to cause cancer, and
DIDP, which is known to the State of California to cause	DIDP, which is known to the State of California to cause Birth Defects or other

Birth Defects or other reproductive harm.	reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------