

SITOP PSU300B/3AC/24VDC/30A

\*\*\*\*\* spare part \*\*\*\*\* SITOP PSU300B 30 A stabilized power supply input: 400-500 V 3 AC output: 24 V DC/30 A successor: 6EP3437-8UB00-0AY0



input	
type of the power supply network	3-phase AC
supply voltage at AC	
<ul style="list-style-type: none"> <li>• minimum rated value</li> <li>• maximum rated value</li> <li>• initial value</li> <li>• full-scale value</li> </ul>	400 V 500 V 320 V 575 V
wide range input	Yes
buffering time for rated value of the output current in the event of power failure minimum	20 ms
operating condition of the mains buffering	at $V_{in} = 400\text{ V}$
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
input current	
<ul style="list-style-type: none"> <li>• at rated input voltage 400 V</li> <li>• at rated input voltage 500 V</li> </ul>	1.6 A 1.3 A
current limitation of inrush current at 25 °C maximum	56 A
I <sup>2</sup> t value maximum	2.24 A <sup>2</sup> ·s
fuse protection type	none
fuse protection type in the feeder	Required: 3-pole connected miniature circuit breaker 10 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489)
output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
<ul style="list-style-type: none"> <li>• at output 1 at DC rated value</li> </ul>	24 V
output voltage adjustable	Yes; via potentiometer
adjustable output voltage	24 ... 28.8 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
<ul style="list-style-type: none"> <li>• on slow fluctuation of input voltage</li> <li>• on slow fluctuation of ohm loading</li> </ul>	0.1 % 0.1 %
residual ripple	
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	100 mV
voltage peak	
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	200 mV
display version for normal operation	Green LED for 24 V OK
type of signal at output	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for "24 V OK"
behavior of the output voltage when switching on	No overshoot of $V_{out}$ (soft start)
response delay maximum	2.5 s

voltage increase time of the output voltage	
• maximum	500 ms
output current	
• rated value	30 A
• rated range	0 ... 30 A; +60 ... +70 °C: Derating 1.7%/K
supplied active power typical	960 W
constant overload current	
• on short-circuiting during the start-up typical	32 A
• at short-circuit during operation typical	32 A
bridging of equipment	Yes; switchable characteristic
number of parallel-switched equipment resources for increasing the power	2
<b>efficiency</b>	
efficiency in percent	93 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	50 W
<b>closed-loop control</b>	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	1 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	3 %
setting time	
• maximum	10 ms
<b>protection and monitoring</b>	
design of the overvoltage protection	< 35 V
property of the output short-circuit proof	Yes
design of short-circuit protection	Alternatively, constant current characteristic approx. 32 A or latching shutdown
• typical	32 A
enduring short circuit current RMS value	
• typical	32 A
display version for overload and short circuit	LED yellow for "overload", LED red for "latching shutdown"
<b>safety</b>	
galvanic isolation between input and output	Yes
galvanic isolation	Output voltage: SELV, ES1 (IEC 62368-1), DVC As (IEC 61204-7)
operating resource protection class	Class I
leakage current	
• maximum	3.5 mA
protection class IP	IP20
<b>EMC</b>	
standard	
• for emitted interference	EN 55022 Class B
• for mains harmonics limitation	EN 61000-3-2
• for interference immunity	EN 61000-6-2
<b>standards, specifications, approvals</b>	
certificate of suitability	
• CE marking	Yes
• UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
• EAC approval	Yes
• NEC Class 2	No
type of certification	
• CB-certificate	No
MTBF at 40 °C	885 739 h
<b>standards, specifications, approvals hazardous environments</b>	
certificate of suitability	
• IECEx	No
• ATEX	No
• ULhazloc approval	No
• FM registration	No
<b>standards, specifications, approvals marine classification</b>	

shipbuilding approval	No
Marine classification association	
<ul style="list-style-type: none"> <li>American Bureau of Shipping Europe Ltd. (ABS)</li> </ul>	No
<ul style="list-style-type: none"> <li>French marine classification society (BV)</li> </ul>	No
<ul style="list-style-type: none"> <li>Det Norske Veritas (DNV)</li> </ul>	No
<ul style="list-style-type: none"> <li>Lloyds Register of Shipping (LRS)</li> </ul>	No
<b>ambient conditions</b>	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-25 ... +70 °C; with natural convection
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +85 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
<b>connection method</b>	
type of electrical connection	screw terminal
<ul style="list-style-type: none"> <li>at input</li> </ul>	L1, L2, L3, PE: 1 screw terminal each for 0.2 ... 4 mm <sup>2</sup> single-core/finely stranded
<ul style="list-style-type: none"> <li>at output</li> </ul>	+, -: 2 screw terminals each for 0.33 ... 10 mm <sup>2</sup>
<ul style="list-style-type: none"> <li>for auxiliary contacts</li> </ul>	13, 14 (alarm signal): 1 screw terminal each for 0.14 ... 1.5 mm <sup>2</sup>
<b>mechanical data</b>	
width × height × depth of the enclosure	150 × 125 × 150 mm
installation width × mounting height	150 mm × 225 mm
required spacing	
<ul style="list-style-type: none"> <li>top</li> </ul>	50 mm
<ul style="list-style-type: none"> <li>bottom</li> </ul>	50 mm
<ul style="list-style-type: none"> <li>left</li> </ul>	0 mm
<ul style="list-style-type: none"> <li>right</li> </ul>	0 mm
fastening method	Snaps onto DIN rail EN 60715 35x15
<ul style="list-style-type: none"> <li>DIN-rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>S7 rail mounting</li> </ul>	No
<ul style="list-style-type: none"> <li>wall mounting</li> </ul>	No
housing can be lined up	Yes
net weight	3.4 kg
<b>accessories</b>	
electrical accessories	Buffer module
mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
<b>further information internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>to web page: selection aid TIA Selection Tool</li> </ul>	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
<ul style="list-style-type: none"> <li>to website: CAx-Download-Manager</li> </ul>	<a href="https://siemens.com/cax">https://siemens.com/cax</a>
<ul style="list-style-type: none"> <li>to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>additional information</b>	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
<b>security information</b>	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a> . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a> . (V4.7)

## Classifications

	Version	Classification
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	10	EC002540
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

## Approvals Certificates

### General Product Approval

[Manufacturer Declaration](#)

[Declaration of Conformity](#)



[China RoHS](#)



last modified:

3/26/2026 