


Product datasheet

Specifications

Short terminal shield, GoPact MCCB 125, 3 poles



G12STSHD3P

Main

Range of product	GoPact MCCB
Product or component type	Short terminal shield
Device application	Insulation
Range compatibility	GoPact MCCB 125
Poles description	3P
Quantity	2

Complementary

Localisation on device	Upstream Downstream
IP degree of protection	IP40 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.6 cm
Package 1 Width	6.1 cm
Package 1 Length	15.6 cm
Package 1 Weight	0.2 kg
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.4 kg
Unit Type of Package 3	P06
Number of Units in Package 3	160
Package 3 Height	149 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	47 kg

Contractual warranty



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Take-back	No
-----------	----

Technical Illustration

Dimensions

