



Figure similar

line commutating reactor for rectifier; phases: 3; Un1(V): 500; I<sub>thmax</sub> 1(A) / F1(Hz): 112 /50; I<sub>LN</sub> (A): 100.8; UK(%): 4; LN(MH): 0.261; temperature rise/insulation class: 40 /H; IP00; connection: flat-type; EN 61558-2-20 >reactor<

General technical data		
product designation		Kommut.-Drossel f. Stromrichter
phase number		3
type of voltage		AC
operating voltage rated value	V	500
operating frequency rated value	Hz	50
<ul style="list-style-type: none"> <li>• — operational current at AC rated value</li> <li>— current at AC maximum</li> <li>• current at DC rated value</li> </ul>	A	100.8
	A	112
	A	137.19
peak current	A	140
inductivity rated value	H	0.00026
relative inductive drop in voltage for rated value of the current, voltage and frequency	%	4
power loss [W] of the coil	W	135
power loss [W] of the iron core	W	52
Mechanical data		
type of electrical connection for main current circuit		flat connector
width	m	0.225
height	m	0.21
depth	m	0.16
Ambient conditions		
thermal class according to IEC 60085		H
ambient temperature rated value	°C	40
protection class IP		IP00
Certificates/ approvals		
General Product Approval	other	Environment



[Confirmation](#)



[Environmental Confirmations](#)

### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4EU2522-7BA00-0AA0>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4EU2522-7BA00-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4EU2522-7BA00-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=4EU2522-7BA00-0AA0&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4EU2522-7BA00-0AA0&lang=en)

---

last modified:

5/9/2026 