



SIPLUS S7-1500 AI 8xU/I HF based on 6ES7531-7NF00-0AB0 with conformal coating, -40...+70 °C, start up -25 °C, analog input module 16-bit resolution, accuracy 0.1%, 8 channels in groups of 1, common mode voltage: 30 V AC/60 V DC, diagnostics; hardware interrupts; including infeed element, shielding bracket and shield terminal

| General information   |                                    |
|---|------------------------------------|
| Product type designation  | AI 8xU/I HF                        |
| Firmware version  |                                    |
| • FW update possible  | Yes                                |
| based on  | <a href="#">6ES7531-7NF00-0AB0</a> |
| Product function  |                                    |
| • I&M data  | Yes; I&M0 to I&M3                  |
| • Isochronous mode  | No                                 |
| • Prioritized startup   | Yes                                |
| • Measuring range scalable  | No                                 |
| • Scalable measured values  | Yes                                |
| • Adjustment of measuring range                                       | Yes                                |
| Engineering with  |                                    |
| • STEP 7 TIA Portal configurable/integrated from version              | see entry ID: 109746275            |
| Operating mode  |                                    |
| • Oversampling  | No                                 |
| • MSI   | Yes                                |
| CiR - Configuration in RUN  |                                    |
| Reparameterization possible in RUN                                    | Yes                                |
| Calibration possible in RUN   | Yes                                |
| Supply voltage  |                                    |
| Rated value (DC)  | 24 V                               |
| permissible range, lower limit (DC)                                   | 19.2 V                             |
| permissible range, upper limit (DC)                                   | 28.8 V                             |
| Reverse polarity protection   | Yes                                |
| Input current   |                                    |
| Current consumption, max.   | 50 mA; with 24 V DC supply         |
| Power   |                                    |
| Power consumption from the backplane bus                              | 0.85 W                             |
| Power loss  |                                    |
| Power loss, typ.  | 1.9 W                              |
| Analog inputs   |                                    |
| Number of analog inputs   | 8                                  |
| • For current measurement   | 8                                  |
| • For voltage measurement   | 8                                  |
| permissible input voltage for voltage input (destruction limit), max. | 28.8 V                             |
| permissible input current for current input (destruction limit), max. | 40 mA                              |

| Input ranges (rated values), voltages               |  |
|---|--|
| • 0 to +5 V   | No   |
| • 0 to +10 V  | No   |
| • 1 V to 5 V  | Yes  |
| — Input resistance (1 V to 5 V)                     | 100 kΩ   |
| • -10 V to +10 V                                    | Yes  |
| — Input resistance (-10 V to +10 V)                 | 100 kΩ   |
| • -2.5 V to +2.5 V                                  | Yes  |
| — Input resistance (-2.5 V to +2.5 V)               | 100 kΩ   |
| • -25 mV to +25 mV                                  | No   |
| • -250 mV to +250 mV                                | No   |
| • -5 V to +5 V                                      | Yes  |
| — Input resistance (-5 V to +5 V)                   | 100 kΩ   |
| • -50 mV to +50 mV                                  | No   |
| • -500 mV to +500 mV                                | No   |
| • -80 mV to +80 mV                                  | No   |
| Input ranges (rated values), currents               |  |
| • 0 to 20 mA  | Yes  |
| — Input resistance (0 to 20 mA)                     | 25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC |
| • -20 mA to +20 mA                                  | Yes  |
| — Input resistance (-20 mA to +20 mA)               | 25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC |
| • 4 mA to 20 mA                                     | Yes  |
| — Input resistance (4 mA to 20 mA)                  | 25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC |
| Input ranges (rated values), thermocouples          |  |
| • type B  | No   |
| • type C  | No   |
| • Type E  | No   |
| • Type J  | No   |
| • Type K  | No   |
| • Type L  | No   |
| • Type N  | No   |
| • Type R  | No   |
| • Type S  | No   |
| • Type T  | No   |
| • Type TXK/TXK(L) to GOST                           | No   |
| Input ranges (rated values), resistance thermometer |  |
| • Cu 10   | No   |
| • Cu 10 according to GOST                           | No   |
| • Cu 50   | No   |
| • Cu 50 according to GOST                           | No   |
| • Cu 100  | No   |
| • Cu 100 according to GOST                          | No   |
| • Ni 10   | No   |
| • Ni 10 according to GOST                           | No   |
| • Ni 100  | No   |
| • Ni 100 according to GOST                          | No   |
| • Ni 1000   | No   |
| • Ni 1000 according to GOST                         | No   |
| • LG-Ni 1000  | No   |
| • Ni 120  | No   |
| • Ni 120 according to GOST                          | No   |
| • Ni 200  | No   |
| • Ni 200 according to GOST                          | No   |
| • Ni 500  | No   |
| • Ni 500 according to GOST                          | No   |
| • Pt 10   | No   |
| • Pt 10 according to GOST                           | No   |
| • Pt 50   | No   |
| • Pt 50 according to GOST                           | No   |

|  |   |
|--|---|
| • Pt 100   | No  |
| • Pt 100 according to GOST   | No  |
| • Pt 1000  | No  |
| • Pt 1000 according to GOST  | No  |
| • Pt 200   | No  |
| • Pt 200 according to GOST   | No  |
| • Pt 500   | No  |
| • Pt 500 according to GOST   | No  |
| <b>Input ranges (rated values), resistors</b>  |   |
| • 0 to 150 ohms  | No  |
| • 0 to 300 ohms  | No  |
| • 0 to 600 ohms  | No  |
| • 0 to 3000 ohms   | No  |
| • 0 to 6000 ohms   | No  |
| • PTC  | No  |
| <b>Cable length</b>  |   |
| • shielded, max.   | 800 m   |
| <b>Analog value generation for the inputs</b>  |   |
| <b>Integration and conversion time/resolution per channel</b>  |   |
| • Resolution with overrange (bit including sign), max.   | 24 bit; When using the function "Scaling of the measured values" or "Measuring range adaptation" (32 bit REAL format); 16 bit when using the S7 format (16 bit INTEGER) |
| • Integration time, parameterizable  | Yes   |
| • Integration time (ms)  | Fast mode: 2.5 / 16.67 / 20 / 100 ms, standard mode: 7.5 / 50 / 60 / 300 ms   |
| • Basic conversion time, including integration time (ms)   | Fast mode: 4 / 18 / 22 / 102 ms; Standard mode: 9 / 52 / 62 / 302 ms  |
| • Interference voltage suppression for interference frequency f1 in Hz   | 400 / 60 / 50 / 10 Hz   |
| • Basic execution time of the module (all channels released)   | Corresponds to the channel with the highest basic conversion time   |
| <b>Smoothing of measured values</b>  |   |
| • parameterizable  | Yes   |
| • Step: None   | Yes   |
| • Step: low  | Yes   |
| • Step: Medium   | Yes   |
| • Step: High   | Yes   |
| <b>Encoder</b>   |   |
| <b>Connection of signal encoders</b>   |   |
| • for voltage measurement  | Yes   |
| • for current measurement as 2-wire transducer   | Yes; with external transmitter supply   |
| • for current measurement as 4-wire transducer   | Yes   |
| • for resistance measurement with two-wire connection  | No  |
| • for resistance measurement with three-wire connection  | No  |
| • for resistance measurement with four-wire connection   | No  |
| <b>Errors/accuracies</b>   |   |
| Linearity error (relative to input range), (+/-)   | 0.04 %  |
| Temperature error (relative to input range), (+/-)   | 0.01 %/K  |
| Crosstalk between the inputs, max.   | -80 dB  |
| Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)  | 0.02 %  |
| <b>Operational error limit in overall temperature range</b>  |   |
| • Voltage, relative to input range, (+/-)  | 0.2 %   |
| • Current, relative to input range, (+/-)  | 0.2 %   |
| <b>Basic error limit (operational limit at 25 °C)</b>  |   |
| • Voltage, relative to input range, (+/-)  | 0.05 %  |
| • Current, relative to input range, (+/-)  | 0.05 %  |
| <b>Interference voltage suppression for <math>f = n \times (f1 \pm 1 \%)</math>, f1 = interference frequency</b> |   |
| • Series mode interference (peak value of interference < rated value of input range), min.                       | 80 dB; in the Standard operating mode, 40 dB in the Fast operating mode   |
| • Common mode voltage, max.  | 60 V DC/30 V AC   |
| • Common mode interference, min.   | 80 dB   |

| Interrupts/diagnostics/status information                           |   |
|---|---|
| Diagnostics function  | Yes   |
| Alarms  |   |
| • Diagnostic alarm  | Yes   |
| • Limit value alarm   | Yes; two upper and two lower limit values in each case  |
| Diagnoses   |   |
| • Monitoring the supply voltage                                     | Yes   |
| • Wire break  | Yes; only for 1 ... 5 V and 4 ... 20 mA   |
| • Overflow/Underflow  | Yes   |
| Diagnostics indication LED  |   |
| • RUN LED   | Yes; green LED  |
| • ERROR LED   | Yes; red LED  |
| • Monitoring of the supply voltage (PWR-LED)                        | Yes; green LED  |
| • Channel status display  | Yes; green LED  |
| • for channel diagnostics   | Yes; red LED  |
| • for module diagnostics  | Yes; red LED  |
| Potential separation  |   |
| Potential separation channels                                       |   |
| • between the channels  | Yes   |
| • between the channels, in groups of                                | 1   |
| • between the channels and backplane bus                            | Yes   |
| • between the channels and the power supply of the electronics      | Yes   |
| Permissible potential difference                                    |   |
| between different circuits  | 60 V DC/30 V AC; insulation rated for 120 V AC basic insulation: between the channels and the supply voltage L+; between the channels and the backplane bus; between the channels   |
| Isolation   |   |
| Isolation tested with   | 2 000 V DC between the channels and the supply voltage L+; 2 000 V DC between the channels and the backplane bus; 2 000 V DC between the channels; 707 V DC (type test) between the supply voltage L+ and the backplane bus |
| Standards, approvals, certificates                                  |   |
| Ecological footprint  |   |
| • environmental product declaration                                 | Yes   |
| Global warming potential  |   |
| — global warming potential, (total) [CO2 eq]                        | 38.6 kg   |
| — global warming potential, (during production) [CO2 eq]            | 14.4 kg   |
| — global warming potential, (during operation) [CO2 eq]             | 24.6 kg   |
| — global warming potential, (after end of life cycle) [CO2 eq]      | -0.44 kg  |
| Security  |   |
| signed firmware update  | No  |
| data integrity  | No  |
| Ambient conditions  |   |
| Ambient temperature during operation                                |   |
| • horizontal installation, min.                                     | -40 °C; = Tmin (incl. condensation/frost)   |
| • horizontal installation, max.                                     | 70 °C; = Tmax   |
| • vertical installation, min.                                       | -40 °C; = Tmin  |
| • vertical installation, max.                                       | 40 °C; = Tmax   |
| Altitude during operation relating to sea level                     |   |
| • Installation altitude above sea level, max.                       | 5 000 m   |
| • Ambient air temperature-barometric pressure-altitude              | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)             |
| Relative humidity   |   |
| • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation   |
| Resistance  |   |
| Coolants and lubricants   |   |

|   |   |                       |
|---|---|-----------------------|
| — Resistant to commercially available coolants and lubricants   | Yes; Incl. diesel and oil droplets in the air   |                       |
| <b>Use in stationary industrial systems</b>   |   |                       |
| — to biologically active substances according to EN 60721-3-3   | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request  |                       |
| — to chemically active substances according to EN 60721-3-3   | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |                       |
| — to mechanically active substances according to EN 60721-3-3   | Yes; Class 3S4 incl. sand, dust, *  |                       |
| <b>Use on ships/at sea</b>  |   |                       |
| — to biologically active substances according to EN 60721-3-6   | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request   |                       |
| — to chemically active substances according to EN 60721-3-6   | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |                       |
| — to mechanically active substances according to EN 60721-3-6   | Yes; Class 6S3 incl. sand, dust; *  |                       |
| <b>Usage in industrial process technology</b>   |   |                       |
| — Against chemically active substances acc. to EN 60654-4   | Yes; Class 3 (excluding trichlorethylene)   |                       |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04  | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |                       |
| <b>Remark</b>   |   |                       |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04   | * The supplied plug covers must remain in place over the unused interfaces during operation!  |                       |
| <b>Conformal coating</b>  |   |                       |
| <ul style="list-style-type: none"> <li>• Coatings for printed circuit board assemblies acc. to EN 61086</li> <li>• Protection against fouling acc. to EN 60664-3</li> <li>• Military testing according to MIL-I-46058C, Amendment 7</li> <li>• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A</li> </ul> | <p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p>     |                       |
| <b>Dimensions</b>   |   |                       |
| Width   | 35 mm   |                       |
| Height  | 147 mm  |                       |
| Depth   | 129 mm  |                       |
| <b>Weights</b>  |   |                       |
| Weight, approx.   | 280 g   |                       |
| <b>Classifications</b>  |   |                       |
|   | <b>Version</b>  | <b>Classification</b> |
| eClass  | 14  | 27-24-22-01           |
| eClass  | 12  | 27-24-22-01           |
| eClass  | 9.1   | 27-24-22-01           |
| eClass  | 9   | 27-24-22-01           |
| eClass  | 8   | 27-24-22-01           |
| eClass  | 7.1   | 27-24-22-01           |
| eClass  | 6   | 27-24-22-01           |
| ETIM  | 10  | EC001420              |
| ETIM  | 9   | EC001420              |
| ETIM  | 8   | EC001420              |
| ETIM  | 7   | EC001420              |
| IDEA  | 4   | 3562                  |
| UNSPSC  | 15  | 32-15-17-05           |
| <b>Approvals / Certificates</b>   |   |                       |
| <b>General Product Approval</b>   |   |                       |

[China RoHS](#)



[Manufacturer Declaration](#)



General Product Approval

EMV

For use in hazardous locations

[China RoHS](#)



For use in hazardous locations

Maritime application

Environment



last modified:

10/23/2025