

# Product data sheet

Specifications



## ASCO 3044 Load Bank

ASCOLBLV3044

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

### Main

Product Type Resistive load bank

### Complementary

Voltage Rating  
380 V AC 50 Hz  
400 V AC 50 Hz  
415 V AC 50 Hz  
440 V AC 60 Hz  
480 V AC 60 Hz

Capacity Rating  
380 kW  
400 kW  
425 kW  
430 kW

Load Step Resolution 1 kW

Cooling System Rating 3899064.4 Gal/hr(US) (14759.3 m3/h)

Provided Equipment  
1 gland plate  
HRC fuse  
Cooling fans

Enclosure Material Zintec

Surface Finish Zinc plated

Color Gray RAL 7042)

Connection Terminals Terminals inside)

Length 53.7 in (1364 mm)

Width 46.5 in (1180 mm)

Height 65.2 in (1655 mm)

Product Weight 1322.8 lb(US) (600 kg)

### Environment

Ambient Air Temperature 95 °F (35 °C)

Standards  
ISO 9001  
CE

IP Protection  
IP2X  
IP54

### Packing Units

Unit Type of Package 1 PCE

Nbr. of units in pkg. 1

Package 1 Height 53.7 in (136.4 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Package 1 Width</b>	46.5 in (118.0 cm)
<b>Package 1 Length</b>	65.2 in (165.5 cm)
<b>Package weight(Lbs)</b>	1322.8 lb(US) (600.0 kg)

---

## **Contractual warranty**

---

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

### Use Longer



#### Lifetime extension

Repair	No
--------	----