

Product datasheet

Specifications



Closed toroid B type, VigiPacT,
TB210, inner diameter 210mm,
rated current 400A

LV481014

Main

Range	VigiPacT
Device short name	TB210
Product or component type	Earth leakage current sensor
Device application	Equipment monitoring and control
Range compatibility	VigiPacT RHB residual current protection relay VigiPacT RHB wiring kit
current sensor type	B type closed toroid
[Ie] rated operational current	400 A

Complementary

Network frequency	50/60 Hz 0...2000 Hz
[Icw] rated short-time withstand current	25 kA for 0.5 s
Residual short-circuit withstand current	36 kA / 0.5 s conforming to IEC 60947-2
[Ui] rated insulation voltage	800 V
Overvoltage category	III
[Uimp] rated impulse withstand voltage	8 kV
Mounting mode	Fixed (plain backplate)
Connections - terminals	Prefabricated connection
Diameter	210 mm inner:
Net weight	4.290 kg
Height	339 mm
Width	339 mm
Depth	113 mm

Environment

IP degree of protection	Body: IP40 Connectors: IP20
Environmental characteristic	Exposure to damp heat in service: category C2: 48 hours conforming to IEC 60068-2-56 Exposure to damp heat not in service (25...55 °C, RH 95 %) : 28 cycles conforming to IEC 60068-2-30 Salt mist: Kb/2 conforming to IEC 60068-2-52
Pollution degree	Level 2 conforming to IEC 60664-1
Ambient air temperature for operation	-25...70 °C

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for storage	-25...70 °C
Standards	IEC 60947-2
Product certifications	CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.000 cm
Package 1 Width	31.000 cm
Package 1 Length	44.000 cm
Package 1 Weight	4.688 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	3815e14f-1f03-48b5-b486-8328d0da7e28

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins