

Measurement accessories						
Designation	Use	Description	Cable length m (ft)	Unit reference	Sold in lots of (1)	Weight kg/ lb
Temperature control						
NTC probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 68 - Grey - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STNTCRN52015	8	0.144/0.320
				TM1STNTCRN5201P	100	0.144/0.320
			3 (9.84)	TM1STNTCRN52030	5	0.180/0.400
				TM1STNTCRN5203P	50	0.180/0.400
			5 (16.40)	TM1STNTCRN52050	4	0.228/0.500
				TM1STNTCRN5205P	25	0.228/0.500
NTC probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 67 - Black - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STNTCRN61515	8	0.104/0.230
				TM1STNTCRN6151P	100	0.104/0.230
			3 (9.84)	TM1STNTCRN61530	5	0.125/0.280
				TM1STNTCRN6153P	50	0.125/0.280
			5 (16.40)	TM1STNTCRN61550	4	0.164/0.360
				TM1STNTCRN6155P	25	0.164/0.360
NTC probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- FAST - IP 67 - Grey - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STNTCSF44015	8	0.144/0.320
				TM1STNTCSF4401P	100	0.144/0.320
			3 (9.84)	TM1STNTCSF44030	5	0.175/0.390
				TM1STNTCSF4403P	50	0.175/0.390
NTC probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 68 - Grey - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STNTCSN62015	8	0.144/0.320
				TM1STNTCSN6201P	100	0.144/0.320
			3 (9.84)	TM1STNTCSN62030	5	0.175/0.390
				TM1STNTCSN6203P	50	0.175/0.390
			5 (16.40)	TM1STNTCSN62050	4	0.232/0.510
				TM1STNTCSN6205P	25	0.232/0.510
NTC probes with a strap 	Pipe ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 68 - Grey - Equipped with 2 conductor cables for controller side - Equipped with strap	1.5 (4.92)	TM1STNTCTN62015	8	0.152/0.340
				TM1STNTCTN6201P	100	0.152/0.340
			3 (9.84)	TM1STNTCTN62030	5	0.180/0.400
				TM1STNTCTN6203P	50	0.180/0.400
PT1000 probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 68 - Green - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STPTTSN62015	8	0.144/0.320
				TM1STPTTSN6201P	100	0.144/0.320
			3 (9.84)	TM1STPTTSN62030	5	0.175/0.390
				TM1STPTTSN6203P	50	0.175/0.390
			5 (16.40)	TM1STPTTSN62050	4	0.232/0.510
				TM1STPTTSN6205P	25	0.232/0.510
PT1000 probes 	Multi-purpose ■ Temperature control: - 50...+110 °C (-122...+230 °F)	- IP 68 - Green - Equipped with 2 conductor cables for controller side	1.5 (4.92)	TM1STPTTSN52015	8	0.136/0.300
				TM1STPTTSN5201P	100	0.136/0.300
			3 (9.84)	TM1STPTTSN52030	5	0.175/0.390
				TM1STPTTSN5203P	50	0.175/0.390
			5 (16.40)	TM1STPTTSN52050	4	0.232/0.510
				TM1STPTTSN5205P	25	0.232/0.510

(1) The given value is the number of products delivered for one ordered reference.