

Product datasheet

Specifications



protection relay, EasyPact MVS, ETA6G

65579

Main

Range of product	EasyPact MVS
Product or component type	Control unit
Circuit breaker application	Standard Industrial
Poles description	4P 3P
Protected poles description	3D + N/2 3D 4D
Neutral position	Left
Network type	AC
Trip unit name	ETA6G
Trip unit technology	Micro-processor based
Trip unit rating	800...4000 A

Complementary

Network frequency	50/60 Hz
Mounting mode	Drawout Fixed
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
Neutral protection setting	Without protection (3D) 0.5 x Ir (3D + N/2) 1 x Ir (4D)
Trip unit protection functions	LSIG
Protection type	Instantaneous short-circuit protection Short time short-circuit protection Earth fault Overload protection (long time)
Fault indication	Overload Short-circuit Earth fault Internal fault
Long time pick-up adjustment type Ir	Adjustable 9 settings
Long time pick-up adjustment range	0.4...1 x In
Long time delay adjustment type	Adjustable 9 settings
[tr] long-time delay adjustment range	0.5...24 s (6 x Ir), accuracy: 0...- 20 %
Thermal memory	20 minutes before and after tripping

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Short-time pick-up adjustment type Isd	Adjustable 9 settings
[Isd] short-time pick-up adjustment range	1.5...10 x Ir
Short-time delay adjustment type	Adjustable 5 settings
[tsd] short-time delay adjustment range	100...400 ms
Instantaneous pick-up adjustment type li	Adjustable 9 settings
Instantaneous pick-up adjustment range	2...15 x In, accuracy: +/- 10 % Off
Ground-fault time delay adjustment type -tg	Adjustable 5 settings
Ground-fault pick-up adjustment type	Adjustable 9 settings
[tg] ground-fault time delay adjustment range	100...400 ms
[Ig] ground-fault pick-up adjustment range	0.2...1 x In (400 A < In =< 1000 A), accuracy: +/- 10 % 500...1200 x In (In >= 1250 A), accuracy: +/- 10 %
Zone selective interlocking ZSI	With
Display type	Digital display
Type of measurement	Maximum current (I1, I2, I3, In), range: 0.2...1.2 In, accuracy: +/- 1.5 % Instantaneous current (I1, I2, I3, In), range: 0.2...12 In, accuracy: +/- 1.5 % Instantaneous current (Ig), range: 0.2...1 In, accuracy: +/- 10 %
Height	200 mm
Width	55 mm
Depth	75 mm
Net weight	0.213 kg

Environment

Ambient air temperature for operation	-5...70 °C
Ambient air temperature for storage	-25...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	8.000 cm
Package 1 Length	21.500 cm
Package 1 Weight	255.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	15
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.254 kg
Unit Type of Package 3	P06
Number of Units in Package 3	120
Package 3 Height	75.000 cm

Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	42.032 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

Not compliant

SCIP Number

61be20a4-4791-4c48-b5fe-b571b4e53b11

REACH Regulation

[REACH Declaration](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Removable battery

Yes

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins