

Product datasheet

Specifications



miniature circuit breaker - Domae - 1P - 2A - 220...240 V - C curve - 4.5 kA

DOM12251SNI

⚠ Discontinued on: 30 Mar 2022

⚠ Discontinued

Main

| | |
|---------------------------|--|
| Device application | Distribution |
| Range | Domae |
| Product or component type | Miniature circuit-breaker |
| Poles description | 1P |
| Number of protected poles | 1 |
| [In] rated current | 2 A |
| Network type | AC |
| Curve code | C |
| Breaking capacity | 4500 A at 230 V AC 50 Hz conforming to IEC 60898-1 |

Complementary

| | |
|--|----------------------|
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 220...240 V AC 50 Hz |
| Control type | Toggle |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Comb busbar and distribution block compatibility | YES |
| 9 mm pitches | 2 |
| Colour | Grey |

Environment

| | |
|------------------------|------------------------------|
| Standards | SNI 04-6507.1 IEC 60898-1 |
| Product certifications | SNI |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.5 cm |
| Package 1 Width | 1.8 cm |
| Package 1 Length | 8.5 cm |

Package 1 Weight

106 g



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Packaging

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant By Exemption](#)

Halogen-free status

Halogen free product

Use Longer



Lifetime extension

Repair

No