

# Product datasheet

Specifications



## 4 THREADED BARS 250A L1400/ LINERGY BS BB

04172

⚠ Discontinued on: 29 Sept 2022

⚠ Discontinued

### Main

Range	Linergy
Range of product	Linergy
Product or component type	Copper busbar
Product name	Linergy BS
Range compatibility	Prisma Prisma G enclosure Prisma Prisma P enclosure
Busbar description	Flat bar
Quantity per set	Set of 4

### Complementary

Installation direction	Vertical, operating position: rear
installation description	Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
[Ui] rated insulation voltage	1000 V
[Ie] rated operational current	250 A
[Ipk] rated peak withstand current	40 kA
I²t on activation	169000 kA².s
Busbar cross section	20 x 5 mm
Length	1400 mm
Product weight	4.94 kg
Type of busbar connection	M6 threaded hole
Connection pitch	Connection each 25 mm
support thickness	5 mm

### Environment

Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

### Packing Units

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1 1

## Contractual warranty

---

Warranty (in months) 18



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

EU RoHS Directive

[Compliant](#)

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Silicone-free

Yes

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins