

# Product datasheet

Specifications



## busbar EasyPact - 630 A - 12 ways

EZB630W12

⚠ Discontinued on: 1 Aug 2023

⚠ Discontinued

### Main

Range of product	EasyPact
Range	EasyPact
Device short name	busbar
Product or component type	Busbar
Device application	Connection
Range compatibility	EasyPact EasyPact EZB circuit breaker
[In] rated current	630 A
Number of ways	12 ways

### Complementary

[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Ue] rated operational voltage	550 V AC 50/60 Hz
Number of devices	12 (3P) 18 (2P) 36 (1P)
Busbar extension	2 or 4 ways
[Icw] rated short-time withstand current	40 kA for 1 s
Height	590 mm
Width	416 mm
Depth	107 mm

### Environment

Standards	IEC 60439
-----------	-----------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.0 cm
Package 1 Width	44.0 cm
Package 1 Length	62.0 cm
Package 1 Weight	13.75 kg
Unit Type of Package 2	P12

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

---

<b>Number of Units in Package 2</b>	12
<b>Package 2 Height</b>	112.0 cm
<b>Package 2 Width</b>	80.0 cm
<b>Package 2 Length</b>	120.0 cm
<b>Package 2 Weight</b>	177.0 kg

---

## **Contractual warranty**

---

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

EU RoHS Directive

[Compliant](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins