

# Product datasheet

Specifications



## Reversing motor starter combination, TeSys Deca, 0.63-1 A, coil 24 V DC low

GV2DM205BL

EAN Code: 3389110058949

! Discontinued

### Main

Range of product	TeSys
Device short name	GV2DM
Product or component type	Motor starter
Motor starter type	Reversing
Coordination type	Type 1
Poles description	3P
Utilisation category	AC-3
Motor power kW	0.25 kW at 400/415 V AC 50/60 Hz 0.37 kW at 400/415 V AC 50/60 Hz 0.25 kW at 440 V AC 50/60 Hz 0.37 kW at 440 V AC 50/60 Hz
[Uc] control circuit voltage	24 V DC
Magnetic tripping current	13 A

### Complementary

Device composition	1 combination block GV2AF3 1 motor circuit breaker type GV2ME 1 3-pole reversing contactor
Thermal protection adjustment range	0.63...1 A
Rated breaking capacity	Iq 50 kA at 400/415 V conforming to IEC 60947-4-1 Iq 50 kA at 440 V conforming to IEC 60947-4-1 Iq 50 kA at 500 V conforming to IEC 60947-4-1
Net weight	0.963 kg
Height	176.4 mm
Width	90 mm
Depth	99.6 mm

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

### Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No