

Product datasheet

Specifications



Communication module, Modicon M580, IEC 61850, coated

BMENOP0300C

Main

Range of product	Modicon M580
Product or component type	Communication module

Complementary

Product compatibility	M580 PAC
Physical interface	3 Ethernet 10/100BASE-TX
Transmission support medium	ethernet cable
Transmission rate	10 Mbit/s 100 Mbit/s
Communication service	MMS messaging client for IEC 61850 MMS messaging server for IEC 61850 Goose for IEC 61850 Modbus TCP messaging RSTP support IP forwarding
Current consumption	1250 mA at 3.3 V DC internal
Module format	Standard
Net weight	0.24 kg

Environment

Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	0...95 % without condensation
Operating altitude	<= 2000 m
Protective treatment	Conformal coating
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility 2014/34/EU - ATEX directive
Product certifications	CE UL CSA RCM EAC Merchant Navy ATEX zone 2/22 IECEx zone 2/22
Standards	EN/IEC 61131-2

	EN/IEC 61010-2-201 UL 61010-2-201 CSA C22.2 No 61010-2-201 IACS E10 EN/IEC 61000-6-5 interface type 1 and type 2 EN/IEC 61850-3 location G EN/IEC 60079-0
--	---

Environmental characteristic	Gas resistant class Gx conforming to ISA S71.04 Gas resistant class 3C4 conforming to IEC 60721-3-3 Dust resistant class 3S4 conforming to IEC 60721-3-3 Sand resistant class 3S4 conforming to IEC 60721-3-3 Salt resistant level 2 conforming to IEC 68252 Mold growth resistant class 3B2 conforming to IEC 60721-3-3 Fungal spore resistant class 3B2 conforming to IEC 60721-3-3 Hazardous location class I division 2
------------------------------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	11.100 cm
Package 1 Length	11.600 cm
Package 1 Weight	262.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	2
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	528.000 g

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)