


Product data sheet

Specifications



shaft extension PAS4/CAS44 - 1 piece

VW33MF1S37A32

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of product	Lexium linear motion
Product or component type	Shaft journal
Product specific application	To connect an encoder and third-party application specific drive
Accessory / separate part category	Maintenance accessories

Complementary

Product compatibility	PAS 44 linear axis 110 x 110 mm CAS 44 linear axis 110 x 110 mm
Range compatibility	Lexium PAS Lexium CAS
Product weight	0.686 lb(US) (0.311 kg)
Maximum radial force Fr	1300 N
Inertia	0.54 kg.cm²
Torque value	1610.8 lbf.in (182 N.m)

Ordering and shipping details

Category	US1PC5718233
Discount Schedule	PC57
GTIN	3606485220062
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.4 in (6.0 cm)
Package 1 Width	4.7 in (12.0 cm)
Package 1 Length	6.3 in (16.0 cm)
Package weight(Lbs)	14.5 oz (411.0 g)

Contractual warranty

Warranty (in months)	18
----------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No

Use Longer


Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No

Dimensions Drawings

Dimensions



Dimensions in mm

A	B	ØD1	ØD2	ISO 4762 screw (1)
37	9	32	55	M10

Dimensions in in.

A	B	ØD1	ØD2	ISO 4762 screw (1)
1.46	0.35	1.26	2.16	M10