

# Product data sheet

Specifications



## Presence detector, Sedna, 10A, graphite

SDN2000270

❗ Discontinued on: 25 February 2020

❗ End-of-service on: 14 March 2022

❗ Discontinued

### Main

|                              |                             |
|------------------------------|-----------------------------|
| Range                        | Sedna                       |
| Product or component type    | Presence detector           |
| Device application           | Light control               |
| Device presentation          | Mechanism with fixing frame |
| Sensor type                  | PIR                         |
| Colour tint                  | Graphite                    |
| Product specific application | Staircase monitoring        |

### Complementary

|                            |                                 |
|----------------------------|---------------------------------|
| Device mounting            | Flush                           |
| Power range                | 2300 W                          |
| Rated current              | 10 A at 230 V AC 50 Hz          |
| Function available         | Automatic with manual override  |
| Light intensity adjustment | 5...1000 lux                    |
| Time delay                 | 2 s...20 min                    |
| Horizontal detection angle | 0...180 °                       |
| Connections - terminals    | Pillar terminals                |
| Terminal capacity          | 1 cable(s) 2.5 mm <sup>2</sup>  |
| Wire structure             | Flexible<br>Rigid               |
| Wire stripping length      | 8 mm                            |
| Fixing mode                | Screws                          |
| Material of visible parts  | Thermoplastic ABS-UV stabilised |
| Surface finish             | Glossy                          |
| Minimum mounting height    | 1.2 m                           |
| Height                     | 71 mm                           |
| Width                      | 71 mm                           |
| Depth                      | 51.4 mm                         |

|                      |            |
|----------------------|------------|
| Product weight       | 0.09825 kg |
| Depth of visual part | 26.6 mm    |

## Environment

|                                       |           |
|---------------------------------------|-----------|
| Conformity mark                       | CE        |
| IP degree of protection               | IP20      |
| Ambient air temperature for operation | 0...35 °C |
| Product certifications                | GOST-R    |

## Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 7.1 cm |
| Package 1 Width              | 5.2 cm |
| Package 1 Length             | 7.1 cm |
| Package 1 Weight             | 72 g   |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| RoHS exemption information | <a href="#">Yes</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Recommended replacement(s)