

Product datasheet

Specifications



MX shunt trip release, Compact NS 100 to 630, 380 VAC to 415 VAC 50 Hz, 440 VAC to 480 VAC 60 Hz

29388

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

Range	ComPact
Range of product	NS400...630 NS400...630 DC NSF150...250 NS125E NSJ400...600 NS100...250 NB400...600 NS100...250 DC NR400...630 NR100...250
Device short name	MX
Product or component type	Voltage release
Device application	Control
Voltage release type	Shunt trip release
[Uc] control circuit voltage	380...415 V AC 50 Hz 440...480 V AC 60 Hz
Range compatibility	ComPact ComPact NS ComPact Compact NB ComPact Compact NR ComPact Compact NSF ComPact Compact NSJ

Complementary

Operating threshold	0.7...1.1 x Un
Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Auxiliary connection terminal	Screw terminal 0...1.5 mm²

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

Use Better

Materials and Substances	
EU RoHS Directive	Compliant

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins