

Product datasheet

Specifications



20 A 30 mA 1P RCBO 6 kA trip type B (3-5In)

SQOR120B03

⚠ Discontinued on: 17 Nov 2017

⚠ Discontinued

Main

Range of product	Qwikline II
Product or component type	Residual current breaker with overcurrent protection (RCBO)
Poles description	1P
Device location in system	Outgoer

Complementary

[In] rated current	20 A
Network type	AC
[Ue] rated operational voltage	230/240 V AC
Curve code	B
Earth-leakage sensitivity	30 mA
Breaking capacity	6 kA
Connections - terminals	10 mm² tunnel type terminals

Environment

Standards	BS EN 61009
-----------	-------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins