

Product data sheet

Specifications



ASCO 5705 8-Device Annunciator

ASCOCAM5705ANN

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Annunciator

Complementary

Functions Available
Monitor status
History
Alarm
Event Logger
Operating condition of equipment
Energy and alarm reports via email

Number of Devices 8

Voltage Rating
120 V AC
24 V DC

Terminal Type Touchscreen display

Communication Network Type
BACnet IP
Modbus TCP

Encryption Protocol AES 128

Available Connection Types
ETHERNET
RS485 link
Discrete input

Number of Fiber Ports 2

Web/Email Interfaces
FTP/HTTP/HTTPS
SMTP V3

Number of Ethernet Ports 2

Number of USB Ports 2

Device Mounting Wall mounted

Solid State Drive Capacity 128 GB

Height 20.3 in (516 mm)

Width 20.3 in (516 mm)

Depth 8.6 in (219 mm)

Product Weight 45.0 lb(US) (20.4 kg)

Environmental

Standards
UL
CUL
EN/IEC 60068-2-27
EN/IEC 60068-2-64

Controller Operating Temperature -4...140 °F (-20...60 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

HMI Operating Temperature 32...140 °F (0...60 °C)

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	20.3 in (51.6 cm)
Package 1 Width	20.3 in (51.6 cm)
Package 1 Length	8.6 in (21.9 cm)
Package weight(Lbs)	45.0 lb(US) (20.4 kg)

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

Use Longer



Lifetime extension

Repair

No