

Product datasheet

Specifications



Direct rotary handle, TeSys GS, black handle, front mounting, 2 positions I-O, for GS 630 to 800A IEC

GS2AH104

! Discontinued

! Discontinued on: 5 Feb 2025

Main

Range of product	TeSys
Range	TeSys
Device short name	GS2AH
Product or component type	Rotary handle
Range compatibility	TeSys TeSys GS GS2S TeSys TeSys GS GS2T
Type of operating handle	Direct frontal
Handle colour	Black

Complementary

Handle positions	O-I
Rotary handle padlocking	With
Switch rated current	630 A 800 A
Standards	IEC
Net weight	0.48 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	13.0 cm
Package 1 Length	25.0 cm
Package 1 Weight	454.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	10
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.065 kg

Contractual warranty



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

No