

Product datasheet

Specifications



Auxiliary contact, GoPact MCCB 125/200/250, 1 NO/NC contact type, circuit breaker status OF/SD

G12-25AUX240

Main

Range of product	GoPact MCCB
Product or component type	Auxiliary contact
Device short name	OF and SD
Device application	Breaker status monitoring
Range compatibility	GoPact MCCB 125 GoPact MCCB 200 GoPact MCCB 250
Signal contacts composition	1 NO/NC

Complementary

Local signalling	ON/OFF indication for open/close Trip indicator for voltage release indication Trip indicator for electrical fault
Mounting mode	By screws
[Ith] conventional free air thermal current	6 A
[Ue] rated operational voltage	240 V AC
[Ie] rated operational current	AC-12: 6 A at 12 V AC 50/60 Hz AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 48 V AC 50/60 Hz AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 240 V AC 50/60 Hz AC-14: 6 A at 12 V AC 50/60 Hz AC-14: 6 A at 24 V AC 50/60 Hz AC-14: 6 A at 48 V AC 50/60 Hz AC-14: 6 A at 110 V AC 50/60 Hz AC-14: 6 A at 240 V AC 50/60 Hz DC-12: 6 A at 12 V DC DC-12: 5 A at 24 V DC DC-12: 1 A at 48 V DC DC-12: 0.5 A at 110 V DC DC-12: 0.25 A at 220 V DC
Mechanical durability	10000 cycles
Auxiliary connection terminal	Pre-wired 0.5 mm²
Cable length	500 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	8.5 cm
Package 1 Length	4.8 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Weight	600 g
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.041 kg
Unit Type of Package 3	P06
Number of Units in Package 3	720
Package 3 Height	60 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	56.992 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No

Technical Illustration

Dimensions

